Hamilton

making connections beautifully

SL

	Wiring Accessories • Circuit Protection • Smart	Lighting Control & Multi-room Audio			
	LPX1X2VAB-PB				
Linea-Perlina CFX Antique Brass Frame/Polished Brass Front 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Antique Brass					
Item Image	Wiring	Dimensions			
	LOP IS LOP OF TWO MAY SMITCHING THE SAME AND	ELECTRICA CFX LINEA PERLINA CFX 1229 Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer			
Primary Range	Linea-Perlina CFX				
Insert Type	1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way	Switching Dimmer			
Plate Finish	Linea-Perlina CFX Antique Brass Frame/Polished Brass				
Insert Colour	Antique Brass				
EAN13 Barcode	5017504849115				
Dimensions (Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm				
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips				
Minimum Wall Box Depth	35mm				
Wattage	200VA (low voltage)				
Switched Poles	Single				
Current Rating	0.8 Amp				
Voltage	220/250V AC				
Maximum Load	200VA (low voltage) Min Load 25VA				
Mains Frequency	50Hz				
IP Rating	IP2XD				
Contact Gap Minimum	None				
Terminal Capacity 1	2 x 1mm2				
Terminal Capacity 2	2 x 1.5mm2				
Earth Terminal Capacity 1	5 x 1mm2				
Earth Terminal Capacity 2	4 x 1.5mm2				
Earth Terminal Capacity 3	3 x 2.5mm2				
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand				
Earth Terminal Capacity 5	1 x 6mm2				
Product Class 1	Face plate must be earthed				
Ambient Operating Temperature	-5° to +40°C				
Recommended Location	Internal Use Only				
Maximum Installation Altitude	2000m				
Standard/Approval	BS EN 60669-1				
Additional Notes	LEADING EDGE TECHNOLOGY DIMMERS for use with low volta dimming LED lamps de-rated by 75% - please contact our Technic the manufacturer of the transformer to confirm that it is dimmable a	al for compatibility. NOTE: It is recommended to contact			

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LPX1X2VAB-PB

Linea-Perlina CFX Antique Brass Frame/Polished Brass Front 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Antique Brass

	÷ .				
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.		It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.		Correct as at 17 October 2018 08:04 Al E&O		
	toad, Brislington, Bristol, BS4 5NZ Pofice 1 Rushmills, Bedford Road, Northampton NN4 7YB n London No. 941624 VAT Registration No. 222 6607 84		Listed in Trimble	riba product selector	

SL