

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LPX1X60HB-HB

Linea-Perlina CFX Connaught Bronze Frame/Connaught Bronze Front 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Connaught Bronze

Item Image	Wiring	Dimensions	
	Dermore Wiring Lee Propriet Loop In Loop Cut. Two Way Selecting Lee Would and Selecting Selecting Loop In Loop Cut. Two Way Selecting Loop Cut. Two Wa	LINEA PERLINA CFX 1X50 Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer	
Primary Range	Linea-Perlina CFX		
Insert Type	1 gang 600W Resistive Leading Edge Push On-Off Rotary 2	Way Switching Dimmer	
Plate Finish	Linea-Perlina CFX Connaught Bronze Frame/Connaught Bronze		
Insert Colour	Connaught Bronze		
EAN13 Barcode	5017504048679		
Dimensions (Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Wattage	600W		
Switched Poles	Single		
Current Rating	2.5 Amp		
Voltage	220/250V AC		
Maximum Load	600W resistive Min Load 100W		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	N/A		
Terminal Capacity 1	2 x 1mm2		
Terminal Capacity 2	2 x 1.5mm2	_	
Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Face plate must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1	_	
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse I should be de-rated by 25%. When dimming LED lamps de-rated by 25%.		



SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LPX1X60HB-HB

Linea-Perlina CFX Connaught Bronze Frame/Connaught Bronze Front 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Connaught Bronze

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of cortain finishes	Correct as at 17 October 2018 08:04 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









