

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LPX1XLEDITB100AB-AB


Linea-Perlina CFX Antique Brass Frame/Antique Brass 1g 100W LED 2 Way Push On/Off Rotary Dimmer Antique Brass

Item Image



Wiring

**Dimensions** 



| Primary Range   | Linea-Perlina CFX  |  |
|---|--|--|
| Insert Type   | 1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer  |  |
| Plate Finish  | Linea-Perlina CFX Antique Brass Frame/Antique Brass  |  |
| Insert Colour   | Antique Brass  |  |
| EAN13 Barcode   | 5017504083670  |  |
| Dimensions (Nominal)  | Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm   |  |
| Weight  | 248 GR   |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |  |
| Minimum Wall Box Depth  | 35mm   |  |
| Wattage   | 5-100W (10 LED Lamps MAX)  |  |
| Switched Poles  | Single   |  |
| Current Rating  | 0.4A   |  |
| Voltage   | 230V-240V  |  |
| Maximum Load  | 5-100W (10 LED Lamps MAX)  |  |
| Mains Frequency   | 50Hz   |  |
| IP Rating   | IP2XD  |  |
| Terminal Capacity 1   | 2X1mm²   |  |
| Terminal Capacity 2   | 2X1.5mm²   |  |
| Earth Terminal Capacity 1   | 5X1mm²   |  |
| Earth Terminal Capacity 2   | 4X1.5mm²   |  |
| Earth Terminal Capacity 3   | 3X2.5mm²   |  |
| Earth Terminal Capacity 4   | 1X4mm² Multi-Strand  |  |
| Earth Terminal Capacity 5   | 1X6mm²   |  |
| Product Class 1   | Face plate muct be earthed   |  |
| Ambient Operating Temperature   | -5°C to +40°C  |  |
| Recommended Location  | Internal Use Only  |  |
| Maximum Installation Altitude   | 2000m  |  |
| Standard/Approval   | BS EN 60669-2-1  |  |
| Additional Notes  | Trailing Edge & Leading Edge Dimmer  |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br>Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing   | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of   | Correct as at 17 October 2018 08:04 AM<br>E&OE   |

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

process and are not binding.















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio