



## LPX1XLEDITB100AB-PB

Linea-Perlina CFX Antique Brass Frame/Polished Brass 1g 100W LED 2 Way Push On/Off Rotary Dimmer Antique Brass

| Item Image  | Wiring   | Dimensions  |
|---|--|---|
|    |  |  <p>Hamilton<br/>LINEA PERLINA CFX<br/>1XLEDITB<br/>LEDITB100 2 Way Dimmer</p>               |
| Primary Range   | Linea-Perlina CFX  |   |
| Insert Type   | 1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer  |   |
| Plate Finish  | Linea-Perlina CFX Antique Brass Frame/Polished Brass   |   |
| Insert Colour   | Antique Brass  |   |
| EAN13 Barcode   | 5017504083687  |   |
| Dimensions (Nominal)  | Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm   |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |   |
| Minimum Wall Box Depth  | 35mm   |   |
| Wattage   | 5-100W (10 LED Lamps MAX)  |   |
| Switched Poles  | Single   |   |
| Current Rating  | 0.4A   |   |
| Voltage   | 230V-240V  |   |
| Maximum Load  | 5-100W (10 LED Lamps MAX)  |   |
| Mains Frequency   | 50Hz   |   |
| IP Rating   | IP2XD  |   |
| Terminal Capacity 1   | 2X1mm <sup>2</sup>   |   |
| Terminal Capacity 2   | 2X1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 1   | 5X1mm <sup>2</sup>   |   |
| Earth Terminal Capacity 2   | 4X1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 3   | 3X2.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 4   | 1X4mm <sup>2</sup> Multi-Strand  |   |
| Earth Terminal Capacity 5   | 1X6mm <sup>2</sup>   |   |
| Product Class 1   | Face plate must be earthed   |   |
| Ambient Operating Temperature   | -5°C to +40°C  |   |
| Recommended Location  | Internal Use Only  |   |
| Maximum Installation Altitude   | 2000m  |   |
| Standard/Approval   | BS EN 60669-2-1  |   |
| Additional Notes  | Trailing Edge & Leading Edge Dimmer  |   |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br>Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 17 October 2018 08:04 AM E&OE   |