



## LPX1XTSEB-EBB

Linea-Perlina CFX Etrium Bronze Frame/Etrium Bronze Front 1 gang Multi-Way Touch Slave Controller Etrium Bronze/Black

| Item Image                    | Wiring                                                                                                                                                                                                                                                           | Dimensions                                                                          |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                               |                                                                                                                                                                                 |  |
| Primary Range                 | Linea-Perlina CFX                                                                                                                                                                                                                                                |                                                                                     |
| Insert Type                   | 1 gang Multi-Way Touch Slave Controller                                                                                                                                                                                                                          |                                                                                     |
| Plate Finish                  | Linea-Perlina CFX Etrium Bronze Frame/Etrium Bronze                                                                                                                                                                                                              |                                                                                     |
| Insert Colour                 | Etrium Bronze/Black                                                                                                                                                                                                                                              |                                                                                     |
| EAN13 Barcode                 | 5017504048839                                                                                                                                                                                                                                                    |                                                                                     |
| Dimensions (Nominal)          | Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm                                                                                                                                                                                                             |                                                                                     |
| Fixing Hole Centres           | Box Fixing = 60.3mm Grid Fixing = CFX Clips                                                                                                                                                                                                                      |                                                                                     |
| Minimum Wall Box Depth        | 35mm                                                                                                                                                                                                                                                             |                                                                                     |
| Wattage                       | The same as Touch Master or Ceiling Dimmer                                                                                                                                                                                                                       |                                                                                     |
| Switched Poles                | N/A                                                                                                                                                                                                                                                              |                                                                                     |
| Current Rating                | The same as Touch Master or Ceiling Dimmer                                                                                                                                                                                                                       |                                                                                     |
| Voltage                       | 220/250V AC                                                                                                                                                                                                                                                      |                                                                                     |
| Maximum Load                  | The same as Touch Master                                                                                                                                                                                                                                         |                                                                                     |
| Mains Frequency               | 50Hz                                                                                                                                                                                                                                                             |                                                                                     |
| IP Rating                     | IP2XD                                                                                                                                                                                                                                                            |                                                                                     |
| Contact Gap Minimum           | N/A                                                                                                                                                                                                                                                              |                                                                                     |
| Terminal Capacity 1           | 2 x 1mm <sup>2</sup>                                                                                                                                                                                                                                             |                                                                                     |
| Terminal Capacity 2           | 2 x 1.5mm <sup>2</sup>                                                                                                                                                                                                                                           |                                                                                     |
| Earth Terminal Capacity 1     | 5 x 1mm <sup>2</sup>                                                                                                                                                                                                                                             |                                                                                     |
| Earth Terminal Capacity 2     | 4 x 1.5mm <sup>2</sup>                                                                                                                                                                                                                                           |                                                                                     |
| Earth Terminal Capacity 3     | 3 x 2.5mm <sup>2</sup>                                                                                                                                                                                                                                           |                                                                                     |
| Earth Terminal Capacity 4     | 1 x 4mm <sup>2</sup> Multi-strand                                                                                                                                                                                                                                |                                                                                     |
| Earth Terminal Capacity 5     | 1 x 6mm <sup>2</sup>                                                                                                                                                                                                                                             |                                                                                     |
| Product Class 1               | Face plate must be earthed                                                                                                                                                                                                                                       |                                                                                     |
| Ambient Operating Temperature | -5° to +40°C                                                                                                                                                                                                                                                     |                                                                                     |
| Recommended Location          | Internal Use Only                                                                                                                                                                                                                                                |                                                                                     |
| Maximum Installation Altitude | 2000m                                                                                                                                                                                                                                                            |                                                                                     |
| Standard/Approval             | BS EN 60669-2-1                                                                                                                                                                                                                                                  |                                                                                     |
| Additional Notes              | Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers |                                                                                     |

## LPX1XTSEB-EBB

### Linea-Perlina CFX Etrium Bronze Frame/Etrium Bronze Front 1 gang Multi-Way Touch Slave Controller Etrium Bronze/Black

|                                                                                                                                                  |                                                                                                                                                                                                                                       |                                                                                                                                                                                        |
|--------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>Patents and Trademarks</p>                                                                                                                    | <p>Linea is a Registered Trade Mark No 2398665<br/>                 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br/>                 Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588</p> |                                                                                                                                                                                        |
| <p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p> | <p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>                                                                                                                          | <p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p> |
| <p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>                | <p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p>                                                                                                                  | <p>Correct as at 17 October 2018 08:05 AM<br/>E&amp;OE</p>                                                                                                                             |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. 14012238