




LPX2J12PB-PBW

Linea-Perlina CFX Polished Brass Frame/Polished Brass Front 2 gang RJ12 Outlet - Unshielded White

Item Image	Wiring	Dimensions																												
	 <table border="1" data-bbox="803 640 966 735"> <thead> <tr> <th>Pin</th> <th>Color</th> <th>Wire Color</th> <th>Socket Color</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>GREEN</td> <td>White</td> <td>BLUE</td> </tr> <tr> <td>2</td> <td>ORANGE</td> <td>White</td> <td>YELLOW</td> </tr> <tr> <td>3</td> <td>WHITE</td> <td>Blue</td> <td>GREEN</td> </tr> <tr> <td>4</td> <td>BLUE</td> <td>White</td> <td>RED</td> </tr> <tr> <td>5</td> <td>WHITE</td> <td>Orange</td> <td>BLACK</td> </tr> <tr> <td>6</td> <td>NO USE</td> <td>Green</td> <td>NO USE</td> </tr> </tbody> </table>	Pin	Color	Wire Color	Socket Color	1	GREEN	White	BLUE	2	ORANGE	White	YELLOW	3	WHITE	Blue	GREEN	4	BLUE	White	RED	5	WHITE	Orange	BLACK	6	NO USE	Green	NO USE	
Pin	Color	Wire Color	Socket Color																											
1	GREEN	White	BLUE																											
2	ORANGE	White	YELLOW																											
3	WHITE	Blue	GREEN																											
4	BLUE	White	RED																											
5	WHITE	Orange	BLACK																											
6	NO USE	Green	NO USE																											

Primary Range	Linea-Perlina CFX
Insert Type	2 gang RJ12 Outlet - Unshielded
Plate Finish	Linea-Perlina CFX Polished Brass Frame/Polished Brass
Insert Colour	White
EAN13 Barcode	5017504870560
Dimensions (Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	N/A
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5 x 1mm ²
Earth Terminal Capacity 2	4 x 1.5mm ²
Earth Terminal Capacity 3	3 x 2.5mm ²
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand
Earth Terminal Capacity 5	1 x 6mm ²
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588

<p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p>	<p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>	<p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p>
<p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>	<p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p>	<p>Correct as at 17 October 2018 08:05 AM E&OE</p>

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com
 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM1238