## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


## LPX45NAB-SBB


Linea-Perlina CFX Antique Brass Frame/Satin Brass Front 1 gang 45A Double Pole Rocker and Neon Red/Black

Wiring



Item Image





**Dimensions** 

| 223323333333333333333333333333333333333   | -  |  |
|---|--|--|
| Primary Range   | Linea-Perlina CFX  |  |
| Insert Type   | 1 gang 45A Double Pole Red Rocker + Neon   |  |
| Plate Finish  | Linea-Perlina CFX Antique Brass Frame/Satin Brass  |  |
| Insert Colour   | Red/Black  |  |
| EAN13 Barcode   | 5017504855710  |  |
| Dimensions (Nominal)  | Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm   |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |  |
| Minimum Wall Box Depth  | 35mm   |  |
| Switched Poles  | Double   |  |
| Current Rating  | 45 Amp   |  |
| Voltage   | 220/250V AC  |  |
| Maximum Load  | 45 Amp   |  |
| Mains Frequency   | 50Hz   |  |
| IP Rating   | IP2XD  |  |
| Contact Gap Minimum   | 3mm  |  |
| Terminal Capacity 1   | 3 x 6mm2   |  |
| Terminal Capacity 2   | 2 x 10mm2  |  |
| Terminal Capacity 3   | 1 x 16mm2  |  |
| Earth Terminal Capacity 1   | 3 x 6mm2   |  |
| Earth Terminal Capacity 2   | 2 x 10mm2  |  |
| Earth Terminal Capacity 3   | 1 x 16mm2  |  |
| Product Class 1   | Must be earthed  |  |
| Ambient Operating Temperature   | -5° to +40°C   |  |
| Recommended Location  | Internal Use Only  |  |
| Maximum Installation Altitude   | 2000m  |  |
| Standard/Approval   | BS EN 60669-1  |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 17 October 2018 08:06 AM<br>E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









