Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio LPX4XTSAB-ABB Linea-Perlina CFX Antique Brass Frame/Antique Brass Front 4 gang Multi-Way Touch Slave Controller Antique Brass/Black Item Image Wiring Dimensions Hamilton 4XTS uch Slave Controller Multi- Way Wiring using Slave module(s) 151.0 i 5 Lamp Neutri SLAVE MODUL Linea-Perlina CFX Primary Range Insert Type 4 gang Multi-Way Touch Slave Controller Plate Finish Linea-Perlina CFX Antique Brass Frame/Antique Brass Insert Colour Antique Brass/Black EAN13 Barcode 5017504861728 Double: Height = 92.0mm Width = 151.0mm Depth = 4.0mm Dimensions (Nominal) **Fixing Hole Centres** Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage The same as Touch Master or Ceiling Dimmer Switched Poles N/A Current Rating The same as Touch Master or Ceiling Dimmer 220/250V AC Voltage Maximum Load The same as Touch Master 50Hz Mains Frequency IP Rating IP2XD Contact Gap Minimum N/A **Terminal Capacity 1** 2 x 1mm2 **Terminal Capacity 2** 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C Ambient Operating Temperature Internal Use Only **Recommended Location** Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be Additional Notes used with Touch Master Dimmers

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LPX4XTSAB-ABB

Linea-Perlina CFX Antique Brass Frame/Antique Brass Front 4 gang Multi-Way Touch Slave Controller Antique Brass/Black

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:06 AM E&OE
	ad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84	Listed in STrimble Product selector DisSPlus CER No. 1997

SL