SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LPX6126AB-ABB

Linea-Perlina CFX Antique Brass Frame/Antique Brass Front 1 gang 10/16A 220/250V AC German Unswitched Socket Black

Item Image Wiring **Dimensions** Hamilton Note: This socket in Non Polarised Linea-Perlina CFX Primary Range Insert Type 1 gang 10/16A 220/250V AC German Unswitched Socket Plate Finish Linea-Perlina CFX Antique Brass Frame/Antique Brass Insert Colour Black EAN13 Barcode 5017504050245 Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None **Current Rating** 10/16 Amp 220/250V AC Voltage Maximum Load 16 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3 x 2 5mm2 Terminal Capacity 2 3 x4mm2 **Terminal Capacity 3** 2 x 6mm2 Multi-Strand Terminal Capacity 4 1 x 10mm2 Product Class 1 Face plate must be earthed **Ambient Operating Temperature** -5° to +40°C Internal Use Only Recommended Location Maximum Installation Altitude 2000m Standard/Approval BS EN ISO 5733 IEC60884-1 Additional Notes Shuttered:Yes Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Patents and Trademarks Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products European standard and the product information is as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:06 AM Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84

NN4 7YB
6607 84

COMMERCIAL AS









