SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **LPXDENTPB-ABW**

Linea-Perlina CFX Polished Brass Frame/Antique Brass Front Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out (DAB Compatible) White

## Item Image Wiring **Dimensions** Hamilton LINEA PERLINA CFX DENT lated TV/FM/Satellite1/Satellite2 Quadplexer 2in/4out Primary Range Linea-Perlina CFX Insert Type Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out (DAB Compatible) Plate Finish Linea-Perlina CFX Polished Brass Frame/Antique Brass Insert Colour White EAN13 Barcode 5017504890087 Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Box Fixing = 60.3mm Grid Fixing = CFX Clips Fixing Hole Centres Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Must be earthed (ref BS7671 415.2.1) Product Class 1 **Ambient Operating Temperature** -5° to +40°C Internal Use Only Recommended Location Maximum Installation Altitude EuroFix Additional Notes Quadplexer for use with combined TV FM and Satellite Signals (DAB compatible) Frequencies 1 TV=5-68 MHz 125-860 MHz Frequencies 2 FM=88-108 MHz Frequencies 3 SAT DC=950-2200 MHz Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Patents and Trademarks Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. European standard and the product information is Therefore, we reserve the right to alter designs correct at the time of going to press. and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 08:07 AM Illustrations and diagrams are reproduced within the limitations of reproduction and printing

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









