



## LPXEURO2PB-SB

Linea-Perlina CFX EuroFix Polished Brass Frame/Satin Brass Front Single Plate complete with 2 EuroFix Apertures 50x50mm and Grid

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|    |   |    |
| Primary Range   | EuroFix   |   |
| Insert Type   | 2 Gang EuroFix 50x50mm Apertured Plate with Grid  |   |
| Plate Finish  | Linea-Perlina CFX EuroFix Polished Brass Frame/Satin Brass  |   |
| Insert Colour   | No Insert Colour  |   |
| EAN13 Barcode   | 5017504889173   |   |
| Dimensions (Nominal)  | Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm  |   |
| Weight  | 194 GR  |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips   |   |
| Minimum Wall Box Depth  | As Per Inserts  |   |
| Switched Poles  | N/A   |   |
| IP Rating   | N/A   |   |
| Contact Gap Minimum   | N/A   |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>  |   |
| Earth Terminal Capacity 2   | 4x1.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand   |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>  |   |
| Product Class 1   | Face plate must be earthed  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Additional Notes  | See EuroFix for a full range of inserts. Plates must be Earthed via the Earth Tag.                            |   |
| Patents and Trademarks  | EuroFix is a Registered Trade Mark No. 2560270  |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.         | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 09:09 AM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM11238