




LPXJ12AB-SBB

Linea-Perlina CFX Antique Brass Frame/Satin Brass Front 1 gang RJ12 Outlet - Unshielded Black

Item Image	Wiring	Dimensions																		
	 <table border="1" data-bbox="808 646 966 730"> <thead> <tr> <th>RIGHT RJ11/12 Wiring colour codes:</th> <th>LEFT RJ11/12 Wiring colour codes:</th> </tr> </thead> <tbody> <tr> <td>NO. 1 NOT USED</td> <td>NO. 1 NOT USED</td> </tr> <tr> <td>2 GREEN / White</td> <td>2 BLUE</td> </tr> <tr> <td>3 ORANGE / White</td> <td>3 YELLOW</td> </tr> <tr> <td>4 WHITE / Blue</td> <td>4 GREEN</td> </tr> <tr> <td>5 BLUE / White</td> <td>5 RED</td> </tr> <tr> <td>6 WHITE / Orange</td> <td>6 BLACK</td> </tr> <tr> <td>7 WHITE / Green</td> <td>7 NOT USED</td> </tr> <tr> <td>8 NOT USED</td> <td>8 NOT USED</td> </tr> </tbody> </table>	RIGHT RJ11/12 Wiring colour codes:	LEFT RJ11/12 Wiring colour codes:	NO. 1 NOT USED	NO. 1 NOT USED	2 GREEN / White	2 BLUE	3 ORANGE / White	3 YELLOW	4 WHITE / Blue	4 GREEN	5 BLUE / White	5 RED	6 WHITE / Orange	6 BLACK	7 WHITE / Green	7 NOT USED	8 NOT USED	8 NOT USED	
RIGHT RJ11/12 Wiring colour codes:	LEFT RJ11/12 Wiring colour codes:																			
NO. 1 NOT USED	NO. 1 NOT USED																			
2 GREEN / White	2 BLUE																			
3 ORANGE / White	3 YELLOW																			
4 WHITE / Blue	4 GREEN																			
5 BLUE / White	5 RED																			
6 WHITE / Orange	6 BLACK																			
7 WHITE / Green	7 NOT USED																			
8 NOT USED	8 NOT USED																			

Primary Range	Linea-Perlina CFX
Insert Type	1 gang RJ12 Outlet - Unshielded
Plate Finish	Linea-Perlina CFX Antique Brass Frame/Satin Brass
Insert Colour	Black
EAN13 Barcode	5017504851552
Dimensions (Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	N/A
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5 x 1mm ²
Earth Terminal Capacity 2	4 x 1.5mm ²
Earth Terminal Capacity 3	3 x 2.5mm ²
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand
Earth Terminal Capacity 5	1 x 6mm ²
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588

<p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p>	<p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>	<p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p>
<p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>	<p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p>	<p>Correct as at 17 October 2018 08:07 AM E&OE</p>

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM12138