

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LPXR212AB-PBB

	Linea-Perlina CFX Antique Brass Frame/Polished Brass Front 1 gang 20AX 2 Way Rocker Antique Brass/Black			
Primary Range Linea-Perlina CFX Insert Type I gang 20X2 Vilva Rocker Plater Flish Linea-Perlina CFX Afrique Brass Frame/Polished Brass Insert Colour Artigue Brass Prame/Polished Brass Insert Colour Artigue Brass Insert Colour	Item Image	Wiring	Dimensions	
Insert Type		Attended 2 vary seatoring Loop in Loop Out Intermediate seatoring	R212 2 Way Rocker	
Pate Finish Linear-Colour Antique Brassa Frame/Polished Brasss Insert Colour Antique Brassa Frame/Polished Brasss Insert Colour Antique Brassa Frame/Polished Brasss Insert Colour Antique Brassa Frame/Polished Brasss Demensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fining Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Current Rating 20AX Voltage 220250V AC Voltage 2202				
Insert Colour Antique Brass/Black 5017504842369 Simms (Nominal) Single, Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Cilps Minimum Wall Box Depth 35mm Simm Grid Fixing = CFX Cilps Minimum Wall Box Depth 35mm Single Current Rating 20AX Voltage 220250V AC Mains Frequency 50Hz IP Rating IP Rating IP Pating	Insert Type	1 gang 20AX 2 Way Rocker		
EAN13 Barcode 5017504942369 Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fixing Hole Centres Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Votage 220/250V AC Maximum Load Amains Frequency IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 3 Terminal Capacity 3 Z x 2.5mm2 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Z x 4mm2 Multi-strand Earth Terminal Capacity 4 Z x 4mm2 Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 4 Z x 4mm2 Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Termin	Plate Finish	Linea-Perlina CFX Antique Brass Frame/Polished Brass		
Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm	Insert Colour	Antique Brass/Black		
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum 75mminal Capacity 1 5 x 1mm2 75mminal Capacity 2 4 x 1.5mm2 75mminal Capacity 3 2 x 2.5mm2 75mminal Capacity 3 2 x 2.5mm2 75mminal Capacity 4 75mminal Capacity 4 75mminal Capacity 1 75mminal Capacity 1 75mminal Capacity 3 75mminal Capacity 4 75mminal Capacity 4 75mminal Capacity 4 75mminal Capacity 4 75mminal Capacity 5 75mminal Capacity 6 75mminal Capacity 6 75mminal Capacity 1 75mminal Capacity 2 75mminal Capacity 3 75mminal Capacity 3 75mminal Capacity 4 75mminal Capacity 5 75mminal Capacity 6 75mminal Capacity 7 75mminal Capacit	EAN13 Barcode	5017504842369		
Minimum Wall Box Depth Single Current Rating 20AX Votage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz PRating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x mm2 Terminal Capacity 1 5 x mm2 Terminal Capacity 1 4 x 1.5mm2 Terminal Capacity 1 5 x mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 5 x mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5 to 44°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea-Perlina CFX SS2 is a UK Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398665 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2006688 All accessories are manufactured under an accredited No. 2006688 All accessories are manufactured under an accredited Product information and the product information is correct at the time of going to press. All accessories are manufactured under an accredited No. 2006688 BIL in a perl of for development programme. Therefore, we reserve the right to after designs and dimensions of reportations and diagrams are reproduced within the limitations of reproduced within guarantee an access colour methan and shaded of the company to improve products in the initiations of reproduction and printing guarantee an access colour methan and shaded of the company to improve products in the initiations of reproduction and printing guarantee an access colour methan and shaded of the company to improve products the helitations of reproduction and printing guarantee an access colour methan and shaded of the company to im	Dimensions (Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm		
Switched Poles Current Rating 20AX Voltage 202/50V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 5 x 1mm2 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 5 x 1 mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm 5 x 1mm2 Terminal Capacity 1 5 x 1.5mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature 7.5 to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398667 CFX is a Registered Trade Mark No 2398667 Linea - Perina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BS EN 150 0001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice.	Minimum Wall Box Depth	35mm		
Voltage 220/250V AC Maximum Load 20 Amp Inductive Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 2x 2.5mm2 Terminal Capacity 4 2x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 5x 1.5mm2 Earth Terminal Capacity 1 5x 1.5mm2 Earth Terminal Capacity 1 5x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 1x 6mm2 Earth Terminal Capacity 4 2x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 6 1x 6mm2 Froduct Class 1 5x 6mm2 Froduct Class 1 Multi-berand Ambient Operating Temperature 5x 6x 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS En 60669-1 Linea is a Registered Trade Mark No 2398667 Patents and Trademarks Linea -Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All conforms the intrinsions of reproduction and printing Exception was exament the finitions of reproduction and printing Exception Froduction and printing Exception and dimensions without prior notico. Exception Activated Science are anaptactured under an accredited and dimensions without prior notico. Exception Activated Science are anaptactured under an accredited and convenience within the limitations of reproduction and printing Exception Froduction and printing of Exception and dimensions without prior notico. Exception Activated Science are anaptactured under an accredited Science and dimensions without prior notico. Exception Activated Science are anaptactured under an accredited Science and dimensions without prior notico. Exception Activated Science Activated Science Science Science Science Science Science Scie	Switched Poles	Single		
Maximum Load 20 Amp inductive Soltz IP Rating IP Ra	Current Rating	20AX		
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6x 1mm2 Earth Terminal Capacity 2 5x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 5x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFY SSZ is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. BUD to manufacturing processes we cannot Gorrect as at 17 October 2018 08.07 AM guarantee an exact oclour match and shadings of ESCE	Voltage	220/250V AC		
P Rating	Maximum Load	20 Amp inductive		
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 I x 6mm2 Earth Terminal Capacity 5 I x 6mm2 Earth Terminal Capacity 5 I x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacit	Mains Frequency	50Hz		
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Ausiliar 4 Ambient Operating Temperature 5 to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CT/ is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. But the manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Due to manufactured under an accredited SE EN ISO 9001: 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 080.77 AM ERO	IP Rating	IP2XD		
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5-5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea Fersional Capacity 6 Patents All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Billustrations and diagrams are reproduced within the limitations of reproduction and printing Usurantee an exact colour match and shadings of Correct as at 17 October 2018 08:07 AM E&CC	Contact Gap Minimum	3mm		
Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 I x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perfina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dinensions without prior notice. BY HIND OF TAME TO THE PROPOGENERAL STANDARD CORRECT STA	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited as part of our development programme. Therefore, we reserve the night to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:07 AM E&C	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Interminal Capacity 5 Ambient Capacity 5 Ambient Operating Temperature -5° to +40°C Recommended Location Maximum Installation Altitude Standard/Approval Bas En 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 8:07 AM E&C	Terminal Capacity 3	2 x 2.5mm2		
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:07 AM E&C	Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 In x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:07 AM E&OC	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BUILUSTATIONS and diagrams are reproducted within the limitations of reproduction and printing guarantee an exact colour match and shadings of EACE	Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BUILUSTATIONS and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of EXCE Correct as at 17 October 2018 08:07 AM EACH	Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. But to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:07 AM EACE	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:07 AM EAOE	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:07 AM E&OE	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:07 AM E&OE	Product Class 1	Must be earthed		
Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Ullustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E&OE	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing BS EN 60669-1 Linea is a Registered Trade Mark No 2398667 CFX is a Registered Design Certificate No. 2066588 Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 Lit is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 08:07 AM guarantee an exact colour match and shadings of	Recommended Location	Internal Use Only		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Lit is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 08:07 AM guarantee an exact colour match and shadings of	Maximum Installation Altitude	2000m		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 08:07 AM guarantee an exact colour match and shadings of	Standard/Approval	ard/Approval BS EN 60669-1		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	Patents and Trademarks	tents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 17 October 2018 08:07 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio