

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LPXR23AB-SBB

Item Image	Linea-Perlina CFX Antique Brass Frame/Satin Brass Front 3 gang 10AX 2 Way Rocker Antique Brass/Black			
Primary Range Lines-Perlina CFX Insert Type 3 agent 20x X 2 Wys Rooker Peter Frinch Lines Perlina CFX Antique Brass Frame/Satin Brass Insert Odour Antique Brass Black EANT 18 Bracode 55.7754MS2238  EANT 18 Bracode 55.7754MS2338  EANT 18 Bracode 55.				
Insert Type  3 gang 10AX 2 Way Rocker Plate Finish Linea-Perlina CPX Antique Brass Frame/Satin Brass Insert Colour Antique Frans/Black EAN13 Barcode 5017604852238 Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Finish Hole Centres Box Fixing + 6lo Samm Grid Fixing = CPX Clips  Witched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP EXD Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 3 1 x 1.5mm2 Earth Terminal Capacity 3 1 x 1.5mm2 Earth Terminal Capacity 3 1 x 4.1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 8 1 x 1.5mm2 Earth Terminal Capacity 9 1 x 2.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 5 x 1 mm2 Earth Terminal Capacity 3 5 x 1 mm2 Earth Terminal Capacity 4 5 x 1 mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth		Abundhe 2 way switching	R23 2 Way Rocker	
Pate Finish   Linea-Perlina CFX Antique Brass Frame/Satin Brass				
Insert Colour	Insert Type	3 gang 10AX 2 Way Rocker		
EAN13 Barcode   S017504852238	Plate Finish	Linea-Perlina CFX Antique Brass Frame/Satin Brass		
Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 2020/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz PRating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 3 1 x 4.5mm2 Earth Terminal Capacity 3 1 x 5.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity	Insert Colour	Antique Brass/Black		
Fixing Hole Centres   Box Fixing = 60.3mm   Grid Fixing = CFX Clips	EAN13 Barcode	5017504852238		
Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency Feating Patting Patting Patting PizxD Contact Gap Minimum 3mm Terminal Capacity 1 5 5 x 1mm2 Terminal Capacity 1 5 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1mm2 Earth Terminal Capacity 3 5 x 1mm2 Earth Terminal Capacity 3 5 x 2.5mm2 Earth Terminal Capacity 4 5 x 6mm2 Froduct Class 1 Ambient Operating Temperature 5 x 6 x 40°C Crecomended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea-Perlina CFX SS 22 is a UK Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS 22 is a UK Registered Design Certificate No. 206688  All accessories are manufactured under an accredited BS EN EG 9001: 2015 Quality Abrangement System.  The Institutions and diagrams are reproduced within the limitations of reproduced within guarantee are accredited and association and controlled.  Earth Institutions and diagrams are reproduced within the limitations of reproduced and reproduced and reproduced and diagrams are reproduced within guarantee are accessed one make and and shadings of	Dimensions (Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm		
Switched Poles Current Rating 10AX Voltage 120/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 2 1 x 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 7 Earth Te	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating  Voltage  220/250 V AC  Maximum Load  Maximum Load  10 Amp inductive  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  5 x 1mm2  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 8  Earth Terminal Capacity 9  In x 6mm2  Earth Terminal Capacity 9  Earth Terminal Capacity 1  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Ca	Minimum Wall Box Depth	25mm		
Voltage 220/250V AC Maximum Load 10 Amp Inductive  Mains Frequency 50Hz P Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5x 1mm2  Terminal Capacity 2 4x 1.5mm2  Terminal Capacity 3 1x 2.5mm2  Terminal Capacity 4 1x 4mm2 Multi-strand  Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 3 3x 2.5mm2  Earth Terminal Capacity 3 1x 4mm2 Multi-strand  Earth Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 6 1x 4mm2 Multi-strand  Earth Terminal Capacity 7 1x 4mm2 Multi-strand  Earth Terminal Capacity 8 1x 4mm2 Multi-strand  Earth Terminal Capacity 9 1x 4mm2 Multi-strand  Earth Terminal Capacity 9 1x 4mm2 Multi-strand  Earth Terminal Capacity 9 1x 6mm2  Fooduct Class 1 1x 6mm2  Fooduct Class 1x 6m	Switched Poles	Single		
Maximum Load  Mains Frequency  50Hz  IP Rating  IP Rati	Current Rating	10AX		
Mains Frequency  Fretting  Frating  Fretting	Voltage	220/250V AC		
PRating   IP2XD	Maximum Load	10 Amp inductive		
Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  I x 4mm2 Multi-strand  Earth Terminal Capacity 5  I x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  I x 6mm2  Earth Terminal Capacity 7  Earth Terminal Capac	Mains Frequency	50Hz		
Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Forduct Class 1 Must be earthed  Ambient Operating Temperature 5-5 to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Business are reproduced within the limitations of reproduction and printing uvarantee an exact colour match and shadings of Correct as at 17 October 2018 80:80.88 Misson of the R&SC	IP Rating	IP2XD		
Terminal Capacity 2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Froduct Class 1  Must be earthed  Ambient Operating Temperature  5-5 to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot the Roce of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without pror notice.  E&CE	Contact Gap Minimum	3mm		
Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Todactive 4  Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perfina CFX SSZ is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited as part of our development programme. Therefore, we reserve the right to after designs and dinarrams are reproduced within the limitations and diagrams are reproduced within guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:08 AM E&CE	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  T x 4mm2 Multi-strand  Earth Terminal Capacity 5  T x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is corect at the time of going to press.  All products listed conform to current British or European standard and the product information is corect at the time of going to press.  All accessories are manufactured under a nacredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:08 AM guarantee an exact colour match and shadings of E&CE	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All approducts listed conform to current British or European standard and the product information is correct at the time of going to press.  All approducts listed conform to current British or European standard and the product information is correct at the time of going to press.  All approducts listed conform to current British or European standard and the product information is correct at the time of going to press.  All approducts listed conform to current British or European standard and the product information is correct at the time of going to press.  All approducts listed conform to current British or European standard and the product information is correct at the time of going to press.  Due to manufacturing processes we cannot the limitations of reproduction and printing  Correct as at 17 October 2018 08:08 AM E&OE	Terminal Capacity 3	1 x 2.5mm2		
Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  I x 4mm2 Multi-strand  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  EXCE	Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:08 AM E&CE	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Tx 4mm2 Multi-strand  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  Fecommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 6069-1  Einea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BLIE All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BLIE All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BLIE All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BLIE All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BLIE All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BLIE All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BLIE All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Correct as at 17 October 2018 08:08 AM Guarantee an exact colour match and shadings of EACE	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But to manufacturing processes we cannot the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM EAOE	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:08 AM guarantee an exact colour match and shadings of	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM guarantee an exact colour match and shadings of	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&OE	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing Tour manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:08 AM E&OE	Product Class 1	Must be earthed		
Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Ullustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&OE	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  BS EN 60669-1  Linea is a Registered Trade Mark No 2398667  Patent No. GB 2383375B  Lit is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 17 October 2018 08:08 AM guarantee an exact colour match and shadings of	Recommended Location	Internal Use Only		
Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 17 October 2018 08:08 AM guarantee an exact colour match and shadings of  E&OE	Maximum Installation Altitude	2000m		
Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&OE	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	Patents and Trademarks	Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 17 October 2018 08:08 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio