




## LPXR26AB-ABB

### Linea-Perlina CFX Antique Brass Frame/Antique Brass Front 6 gang 10AX 2 Way Rocker Antique Brass/Black

| Item Image  | Wiring   | Dimensions  |
|---|--|---|
|    |   |    |
| Primary Range   | Linea-Perlina CFX  |   |
| Insert Type   | 6 gang 10AX 2 Way Rocker   |   |
| Plate Finish  | Linea-Perlina CFX Antique Brass Frame/Antique Brass  |   |
| Insert Colour   | Antique Brass/Black  |   |
| EAN13 Barcode   | 5017504862206  |   |
| Dimensions (Nominal)  | Double: Height = 92.0mm Width = 151.0mm Depth = 4.0mm  |   |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = CFX Clips   |   |
| Minimum Wall Box Depth  | 25mm   |   |
| Switched Poles  | Single   |   |
| Current Rating  | 10AX   |   |
| Voltage   | 220/250V AC  |   |
| Maximum Load  | 10 Amp inductive   |   |
| Mains Frequency   | 50Hz   |   |
| IP Rating   | IP2XD  |   |
| Contact Gap Minimum   | 3mm  |   |
| Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |   |
| Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |   |
| Terminal Capacity 3   | 1 x 2.5mm <sup>2</sup>   |   |
| Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand  |   |
| Terminal Capacity 5   | 1 x 6mm <sup>2</sup>   |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand  |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>   |   |
| Product Class 1   | Must be earthed  |   |
| Ambient Operating Temperature   | -5° to +40°C   |   |
| Recommended Location  | Internal Use Only  |   |
| Maximum Installation Altitude   | 2000m  |   |
| Standard/Approval   | BS EN 60669-1  |   |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B<br>Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.   | Correct as at 17 October 2018 08:08 AM E&OE   |

# Hamilton<sup>®</sup>

making connections beautifully

SL

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio