

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LPXR26PB-PBB

	<u>LPXR26PB-PBB</u> Linea-Perlina CFX Polished Brass Frame/Polished Brass Front 6 gang 10AX 2 Way Rocker Polished Brass/Black			
Primary Range Linea-Peririna CFX Insert Type Garn JAN Z Way Rooker Insert Type Garn JAN Z Way Rooker Palae Finish Dinea-Peririna CFX Insert Type Garn JAN Z Way Rooker Insert Type Garn JAN Z Way Rooker Polland Brissay-Black EAN1 3 Barcode Sot753487205 Debugs Jan	Item Image	Wiring	Dimensions	
Insert Type    6 gang 10AX 2 Way Rocker		Abernative 2 very swetting	R26	
Plate Finish Linear-Colour Polished Brass Plate Annia Barcode Dimensions (Nominal) Double: Height = 92.0mm Width = 151.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth Somm Switched Poles Single Current Rating 10AX Voltage 220250V AC Maximum Load 10 Amp inductive Mains Frequency Fixing Hole Centres Fixing Hole Centres Single Current Rating 10AX Voltage 220250V AC Maximum Load 10 Amp inductive Mains Frequency Fixing Hole Centres Fixing Hole Centres Fixing Contact Gap Minimum Somm Somm Terminal Capacity 1 Fixing Capacity 2 Fixing Capacity 3 Fixing Capacity 4 Fixing Capacity 4 Fixing Capacity 5 Fixing Capacity 5 Fixing Capacity 6 Fixi	Primary Range	Linea-Perlina CFX		
Insert Colour Polished Brass/Black 5017504972205 S017504972205 S01750497205 S0175049720	Insert Type	6 gang 10AX 2 Way Rocker		
EAN13 Barcode 5017504872205 Dimensions (Nominal) Double: Height = 92.0mm Width = 151.0mm Depth = 4.0mm Fixing Hole Centres Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IPZXD Contead Gap Minimum 3mm Feminal Capacity 1 5 x 1 mm2 Terminal Capacity 1 5 x 1 mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 X 1 x 4 mm2 Multi-strand Earth Terminal Capacity 7 X 1 x 4 mm2 Multi-strand Earth Terminal Capacity 8 X 2.5mm2 Earth Terminal Capacity 9 X 2.5mm2 Earth Terminal Capacity 6 X 2.5mm2 Earth Terminal Capacity 7 X 2.5mm2 Earth Terminal Capacity 6 X 2.5mm2 Earth Terminal Capacity 6 X 2.5mm2 Earth Terminal Capacity 7 X 2.5mm2 Earth Terminal Capacity 6 X 2.5mm2 Earth Terminal Capacity 6 X 2.5mm2 Earth Terminal Capacity 7 X 2.5mm2 Earth Terminal Capacity 8 X 2.5mm2 Earth	Plate Finish	Linea-Perlina CFX Polished Brass Frame/Polished Brass		
Dimensions (Nominal)   Double: Height = 92.0mm Width = 151.0mm Depth = 4.0mm	Insert Colour	Polished Brass/Black		
Fixing Hole Centres   Box Fixing = 120.6mm Grid Fixing = CFX Clips	EAN13 Barcode			
Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz PRating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 1 x 2.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 5 x 1mm2 Earth Terminal Capacity 3 5 x 1mm2 Earth Terminal Capacity 4 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Ear	Dimensions (Nominal)	Double: Height = 92.0mm Width = 151.0mm Depth = 4.0mm		
Switched Poles   Single   Current Rating   10AX   Voltage   220/250V AC   Maximum Load   10 Amp inductive   Mains Frequency   50Hz   IP Rating   IP2XD   Contact Gap Minimum   3mm   Terminal Capacity 1   5 x 1mm2   Terminal Capacity 2   4 x 1.5mm2   Terminal Capacity 2   4 x 1.5mm2   Terminal Capacity 4   1 x 4mm2 Multi-strand   Terminal Capacity 4   1 x 4mm2 Multi-strand   Terminal Capacity 5   1 x 6mm2   Earth Terminal Capacity 1   5 x 1mm2   Earth Terminal Capacity 3   3 x 2.5mm2   Earth Terminal Capacity 3   3 x 2.5mm2   Earth Terminal Capacity 5   1 x 6mm2   Earth Terminal Capacity 5   4 x 1.5mm2   Earth Terminal Capacity 5   4 x 4.6mm2   Earth Terminal Capacity 5   1 x 6mm2   Earth Terminal Capacity 6   1 x 6mm2   Earth Terminal Capacity 7 x 6mm2   Earth Terminal Capacity 8   1 x 6mm2   Earth Terminal Capacity 8   1 x 6mm2   Earth Terminal Capacity 9 x 6mm2   Eart	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Cap Minimum 5mm Contact Cap Minimum 5mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 2 4x 1.5mm2 Earth Terminal Capacity 3 1x 2.5mm2 Earth Terminal Capacity 3 1x 2.5mm2 Earth Terminal Capacity 4 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Froduct Class 1 1x 6mm2 F	Minimum Wall Box Depth	25mm		
Voltage 220/250V AC  Maximum Load 10 Amp inductive  Mains Frequency 50Hz  P Rating IPZXD  Contact Gap Minimum 3mm  Terminal Capacity 1 5 x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 1 x 4.1.5mm2  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Froduct Class 1 Must be earthed  Ambient Operating Temperature 5-5 to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Linea is a Registered Trade Mark No 2398667  Patents and Trademarks Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CTX SS2 is a Ukr Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  EXC	Switched Poles	Single		
Maximum Load  Mains Frequency  IP Rating  IP	Current Rating	10AX		
Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity	Voltage	220/250V AC		
IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 1x 2.5mm2  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3x 2.5mm2  Earth Terminal Capacity 3 3x 2.5mm2  Earth Terminal Capacity 4 1x 4mm2 Multi-strand  Earth Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 5 1x 6mm2  Foduct Class 1 Must be earthed  Ambient Operating Temperature 55 to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  Due to manufacturing processes we cannot Therefore, we reserve the right to after designs and dimensions without prior notice.  EXC.  Due to manufacturing processes we cannot Correct as at 17 October 2018 08.08 / EXC.	Maximum Load	10 Amp inductive		
Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Froduct Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  EXTS SS is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Exception of the company to improve products and and dimensions without prior notice.  Exception of the company to improve products and dimensions without prior notice.  Exception of the company to improve products and dimensions without prior notice.  Exception of the company to improve products	Mains Frequency			
Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 4 1 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 1 x 4mm2 Multi-strand  Earth Terminal Capacity 3 1 x 4mm2 Multi-strand  Earth Terminal Capacity 4 1 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Froduct Class 1 Must be earthed  Ambient Operating Temperature 5 to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is cornect at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Possesse we cannot Therefore, we reserve the right to alter designs and dinarensons without prior notice.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of E&C	IP Rating	IP2XD		
Terminal Capacity 2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  1 x 4mm2 Multi-strand  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capac	Contact Gap Minimum	3mm		
Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  I x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  BUSTANDARD		5 x 1mm2		
Terminal Capacity 4  1 x 4mm2 Multi-strand  1 x 6mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Earth Terminal Capacity 5  I x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Maximum Installation Altitude  Standard/Approval  Earth Terminal Capacity 5  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 E&C.	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 6  It is find more than 1	Terminal Capacity 3			
Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 1x 4mm2 Multi-strand  Earth Terminal Capacity 5 1x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks Linea-Perlina CFX SS2 is a UK Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of E&X	Terminal Capacity 4			
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Estandard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Bllustrations and diagrams are reproductod within the limitations of reproduction and printing guarantee an exact colour match and shadings of  Exception of the company to improve products as a part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 A Example of the company to improve products as and dimensions without prior notice.	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  I x 4mm2 Multi-strand  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  Fecommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Estandard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduction and printing guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 ESA				
Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 4mm2 Multi-strand  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BULD TO MARK TO CORD THE COMPANY TO CORD THE PROPRIOR OF THE P	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 A E&C.	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 A E&C.	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 A E&C.	Earth Terminal Capacity 5			
Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:08 A E&C.	Product Class 1			
Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Ullustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 A E&C	Ambient Operating Temperature			
Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 A E&C	Recommended Location			
Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 A E&C	Maximum Installation Altitude			
Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  But is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 17 October 2018 08:08 A  E&C  EACH  Correct as at 17 October 2018 08:08 A  EACH  EACH  Correct as at 17 October 2018 08:08 A  EACH  EACH  Correct as at 17 October 2018 08:08 A  EACH  EACH  Correct as at 17 October 2018 08:08 A  EACH  EACH  Correct as at 17 October 2018 08:08 A  EACH  EACH  EACH  Correct as at 17 October 2018 08:08 A  EACH	Standard/Approval	1 1111		
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GE		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&C	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ	the limitations of reproduction and printing	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:08 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio