

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LPXR312PB-PBW

Item Image  Wiring  Dimensions  Hamiltori  Internation  I	LPXR312PB-PBW  Linea-Perlina CFX Polished Brass Frame/Polished Brass Front 1 gang 20AX Intermediate Rocker Polished Brass/White			
Primary Range Linea-Perlina CFX Insert Type 1 gang 204X Intermediate Rocker Patter Finish Linear Colour Polished Brisso FramePolished Brisso FramePolished Brisso Insert Colour Polished Brisso FramePolished Brisso FrameP			Dimensions	
Insert Type		2 Way Switch  2 Way Switch  1 0 2  1 0 C  Line  Lamp  Neutral	R312 Intermediate Rocker	
Plate Finish	Primary Range	Linea-Perlina CFX		
Insert Colour	Insert Type	1 gang 20AX Intermediate Rocker		
EAN13 Barcode   S017504873349   Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm   Fixing Hote Centres   Box Fixing = 60.3mm Grid Fixing = CFX Clips	Plate Finish	Linea-Perlina CFX Polished Brass Frame/Polished Brass		
Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Smm  Switched Poles Single Current Rating 20AX Voltage 2020/250V AC  Maximum Load 20 Amp inductive Mains Frequency 50Hz Frequency 50Hz Frequency 50Hz Frequency 50Hz Frequency 50Hz Contact Gap Minimum 3mm  Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 3 2 x 4 x 1.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 8mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 9	Insert Colour	Polished Brass/White		
Fixing Hole Centres   Box Fixing = 60.3mm   Grid Fixing = CFX Clips	EAN13 Barcode	5017504873349		
Minimum Wall Box Depth  Switched Poles  Single  Current Rating  20AX  Voltage  220/250V AC  Maximum Load  20 Amp inductive  Mains Frequency  Finance  Finance  Forminal Capacity 1  Forminal Capacity 1  Forminal Capacity 1  Forminal Capacity 2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 3  Z x 2.5mm2  Terminal Capacity 4  Z x 4mm2 Multi-strand  Terminal Capacity 5  Farth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal C	Dimensions (Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm		
Switched Poles Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Term	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating  20AX  Voltage  220/250V AC  Maximum Load  20 Amp inductive  Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  5 x 1mm2  Terminal Capacity 1  5 x 1.5mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  2 x 4.5mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 6  Earth Terminal Capacity 1  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Termina	Minimum Wall Box Depth	35mm		
Voltage 220/250V AC  Maximum Load 20 Amp inductive  Mains Frequency 50Hz  Prating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5x 1mm2  Terminal Capacity 2 4x 1.5mm2  Terminal Capacity 3 2x 2.5mm2  Terminal Capacity 4 2x 4mm2 Multi-strand  Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 5 5x 1.5mm2  Earth Terminal Capacity 5 5x 1.5mm2  Earth Terminal Capacity 6 5x 1.5mm2  Earth Terminal Capacity 7 5x 1.5mm2  Earth Terminal Capacity 8 3x 2.5mm2  Earth Terminal Capacity 9 5x 1.5mm2  Earth Terminal Capacity 9 5x 1.5mm2  Earth Terminal Capacity 1 5x 1.5mm2  Earth Terminal Capacity 1 5x 1.5mm2  Earth Terminal Capacity 5 1x 6mm2  Fooduct Class 1 5x 6mm2  Fooduct Class 1 Must be earthed 4x 6mm2  Ambient Operating Temperature 5x 0x 40x 0x 10x 0x 10x 0x 0	Switched Poles	Single		
Maximum Load  20 Amp inductive  Mains Frequency 50Hz  IP Rating IP	Current Rating	20AX		
Mains Frequency  Freating  Frating  Fresting	Voltage	220/250V AC		
P Rating	Maximum Load	20 Amp inductive		
Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  I x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9	Mains Frequency	50Hz		
Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 2 x 2.5mm2  Terminal Capacity 4 2 x 4mm2 Multi-strand  Terminal Capacity 4 2 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1 Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 6 Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacit	IP Rating	IP2XD		
Terminal Capacity 2  Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 3  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Abbient Operating Temperature  5-5 to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and different programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  E&CE  Linea and Trademarks (Correct as at 17 October 2018 08.08 AM E&CE  E&CE	Contact Gap Minimum	3mm		
Terminal Capacity 3  2 x 2.5mm2  Terminal Capacity 4  2 x 4mm2 Multi-strand  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  I x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SSZ is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited as part of our development programme. Therefore, we reserve the right to after designs and diagrams are reproduced within the limitations and diagrams are reproduced within guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:08 AM E&CE	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 5  T x 6mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 5  T x 6mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 5  T x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under a naccredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot full to the product and shadings of the Correct as at 17 October 2018 08:08 AM guarantee an exact colour match and shadings of E&CE	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Interminal Capacity 5  Ambient Capacity 5  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Bas En 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Design Certificate No. 206588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Bas En ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:08 AM E&OE	Terminal Capacity 3	2 x 2.5mm2		
Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Ix 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  EXCEPTION 18: 17. 18 The Policy of the company to improve products as part of our development programme. Therefore, we reserve the right to later designs and dimensions without prior notice.  Correct as at 17 October 2018 08:08 AM guarantee an exact colour match and shadings of  EXCEPTION 18: 17. 18 Therefore, we reserve the right to slear designs and dimensions without prior notice.	Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&CE	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 6069-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Bllustrations and diagrams are reproducted within the limitations of reproduction and printing guarantee an exact colour match and shadings of EAOE	Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BUILUSTRATION OF Perfoduction and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&OE	Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E&OE	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM guarantee an exact colour match and shadings of	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&OE	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing Tour development programme guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:08 AM E&OE	Product Class 1	Must be earthed		
Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Ullustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&OE	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Design Certificate No. 2066588  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 17 October 2018 08:08 AM guarantee an exact colour match and shadings of	Recommended Location	Internal Use Only		
Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&OE	Maximum Installation Altitude	2000m		
Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&OE	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to after designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 17 October 2018 08:08 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio