

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LPXR32CB-CBB

	Linea-Perlina CFX Copper Bronze Fr	Linea-Perlina CFX Copper Bronze Frame/Copper Bronze Front 2 gang 10AX Intermediate Rocker Copper Bronze/Black			
Primary Range Linea-Perlina CFX Intent Type 2 gans (TAX Intermediate Rocker Plate Finish Linea-Perlina CFX Plate Finish Line	Item Image	Wiring	Dimensions		
Insert Type  2 gang 10AX Intermediate Rocker  Linea-Perlina GPX Copper Bronze Frame/Copper Bronze  Linea-Perlina GPX Copper Bronze Frame/Copper Bronze  Linea-Perlina GPX Copper Bronze Frame/Copper Bronze  EAN13 Barcode  5017504053031  Dimensions (Nominal)  Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  25mm  Single:  Witched Poles  Current Rating  10AX  Voltage  220/250V AC  Maximum Load  10 Amp inductive  Mains Frequency  50Hz  IP Rating  IP PXD  Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  5 x 1 mm2  Earth Terminal Capacity 1  5 x 1 mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  1 x 6mm2  Earth Terminal Capacity 4  1 x 4 mm2 Multi-strand  1 x 4 mm2  Multi-strand  3 x 2.5mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6		2 Way Switch Switch 2 Way Switch	R32 Intermediate Rocker		
Plate Finish Linea-Perlina CFX Copper Bronze Frame/Copper Bronze Linser Colour Copper Bronze Platare CAPATO Sarcode Soft7304059331 Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Zomm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency Fating IP2XD Contact Gap Minimum Jamm Capacity 1 St. Timm2 Terminal Capacity 2 St. Timm2 Terminal Capacity 3 St. X. Simm2 Terminal Capacity 3 St. X. Simm2 Terminal Capacity 4 St. X. Imm2 Earth Terminal Capacity 1 St. X. Imm2 Earth Terminal Capacity 3 St. X. Simm2 Earth Terminal Capacity 4 St. X. Simm2 Earth Terminal Capacity 5 St. X. Simm2 Earth Terminal Capacity 6 St. X. Simm2 Earth Termin	Primary Range	Linea-Perlina CFX			
Sept	Insert Type	2 gang 10AX Intermediate Rocker			
EAN13 Barcode 5017504053031  Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm  Fixing Holo Centres 80x Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth 25mm  Switched Poles Single  Current Rating 10AX  Votage 220250V AC  Maximum Load 10 Amp inductive  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5 x 1mm2  Terminal Capacity 1 5 x 1mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 3 1 x 2.5mm2  Terminal Capacity 3 1 x 4.5mm2  Terminal Capacity 4 1 x 4.5mm2  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 1 5 x 1mm2  Earth Terminal Capacity 3 1 x 4.5mm2  Earth Terminal Capacity 3 1 x 4.5mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 8 1 x 4.15mm2  Earth Terminal Capacity 9 5 x 1 x 6mm2  Earth Terminal Capacity 9 5 x 1 x 6mm2  Earth Terminal Capacity 9 5 x 1 x 6mm2  Earth Terminal Capacity 9 5 x 1 x 6mm2  Earth Terminal Capacity 9 5 x 1 x 6mm2  Earth Terminal Capacity 9 5 x 1 x 6mm2  Earth Terminal Capacity 9 5 x 1 x 6mm2  Earth Terminal Capacity 9 5 x 5 x 6 x 6 x 6 x 6 x 6 x 6 x 6 x 6 x	Plate Finish	Linea-Perlina CFX Copper Bronze Frame/Copper Bronze			
Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fixing Holic Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth Switched Poles Single Current Rating 10.AX Voltage 10.AX Voltage 10.AX Voltage 10.Amp inductive Mains Frequency 10.Amp inductive 10.Amp ind	Insert Colour	Copper Bronze/Black			
Fixing Hole Centres   Box Fixing = 60.3mm   Grid Fixing = CFX Clips	EAN13 Barcode	5017504053031			
Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency Final Rating PRating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 5 x 1mm2 Earth Terminal Capacity 5 6 x 1 x 6mm2 Forduct Class 1 All society of the content of the conte	Dimensions (Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm			
Switched Poles  Current Rating  10AX  Voltage  20259V AC  Maximum Load  10 Amp inductive  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  5x 1mm2  Terminal Capacity 2  4x 1.5mm2  Terminal Capacity 3  1x 2.5mm2  Terminal Capacity 4  1x 4mm2 Multi-strand  Terminal Capacity 5  1x 6mm2  Earth Terminal Capacity 1  5x 1mm2  Earth Terminal Capacity 3  3x 2.5mm2  Earth Terminal Capacity 3  3x 2.5mm2  Earth Terminal Capacity 3  1x 6mm2  Earth Terminal Capacity 3  3x 2.5mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 6  Earth Terminal	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips			
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Ferminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 1 x 4mm2 Multi-strand Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal	Minimum Wall Box Depth	25mm			
Voltage 220/250V AC  Maximum Load 10 Amp inductive  Mains Frequency 50Hz  PRating 1P2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5x 1mm2  Terminal Capacity 2 4x 1.5mm2  Terminal Capacity 3 1x 2.5mm2  Terminal Capacity 3 1x 4.5mm2  Terminal Capacity 4 1x 4mm2 Multi-strand  Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 1 5x 1mm2  Earth Terminal Capacity 3 3x 2.5mm2  Earth Terminal Capacity 3 3x 2.5mm2  Earth Terminal Capacity 3 1x 4.5mm2  Earth Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 5 1x 6mm2  Earth Terminal Capacity 6 1x 6mm2  Earth Terminal Capacity 6 1x 6mm2  Earth Terminal Capacity 7 1x 6mm2  Forduct Class 1 1 5x 6mm2  Forduct Class 1 1 Must be earthed 1x 6mm2  Ambient Operating Temperature 5-5 to 4-40°C  Recommended Location 1x 6mm2  Standard/Approval 1x 6mm2  Earth Standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All cossopries are manufactured under an accredited 8s EN 80 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Switched Poles	Single			
Maximum Load  Mains Frequency 50Hz IP Rating I	Current Rating	10AX			
Mains Frequency  IP Rating  IP2XD  Contact Gap Minimum  3mm  Ferminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  5 x 1mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CEX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Linea Cys Sci 2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of ging to press.  All accessories are manufactured under an accredited as a part of our development programme. Therefore, we reserve the right to after designs and dimensions whitoup prior notice.  BEN ISO 9001: 2015 Quality Management System and dimensions whothout prior notice.  Elond  Correct as at 17 October 2018 808 AN Equarant of the initiations of production and printing quarantee an exact colour match hand shadings of	Voltage	220/250V AC			
IP Rating	Maximum Load	10 Amp inductive			
Contact Gap Minimum  Terminal Capacity 1  5 x 1mm2  Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  I x 6mm2  Earth Terminal Capacity 5  I x 6mm2  Earth Terminal Capacity 5  I x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 8  Earth Terminal Capacity 9	Mains Frequency	50Hz			
Terminal Capacity 2  4 x 1.5mm2  Terminal Capacity 3  1 x 2.5mm2  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 4  1 x 4mm2 Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  Earth Terminal Capacity 5  I x 6mm2  Earth Terminal Capacity 5  I x 6mm2  Earth Terminal Capacity 5  I x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 5  I x 6mm2  Earth Terminal Capacity 6  I x 6mm2  Earth Terminal Capacity 6  Earth Terminal Capacity 6  I x 6mm2  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 8  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Termina	IP Rating	IP2XD			
Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 1  Terminal Capacity 1  Terminal Capacity 2  Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 6  Terminal Capacity 8  Terminal Capacity 9  Terminal	Contact Gap Minimum	3mm			
Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  To found Capacity 5  To found Capacity 5  To found Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Internial Capacity 6  To found Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Zooom  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited SE EN 180 9001 : 2015 Quality Management System.  BS EN 180 9001 : 2015 Quality Management System.  Experimental Capacity 4  To found the product information is as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  BS EN 180 9001 : 2015 Quality Management System.  Experimental Capacity 5  Correct as at 17 October 2018 08:08 At the limitations of reproduction and printing guarantee an exact colour match and shadings of	Terminal Capacity 1	5 x 1mm2			
Terminal Capacity 4  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  To with the search of the sea	Terminal Capacity 2	4 x 1.5mm2			
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot the limitations of reproduction and printing sugarantee an exact colour match and shadings of ESOI	Terminal Capacity 3	1 x 2.5mm2			
Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SSS is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to later designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08.08 AM E&O	Terminal Capacity 4	1 x 4mm2 Multi-strand			
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to going to press.  All accessories are manufactured under an accredited BS EN 150 9001 : 2015 Quality Management System.  But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 8:88 All sparsance and the production and printing guarantee an exact colour match and shadings of	Terminal Capacity 5	1 x 6mm2	1 x 6mm2		
Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  1 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BY ST SS ST S	Earth Terminal Capacity 1	5 x 1mm2			
Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Blustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  E&O  Correct as at 17 October 2018 08:08 All Each of E&O  E&O  Correct as at 17 October 2018 08:08 All Each of E&O  E&O  Correct as at 17 October 2018 08:08 All Each of E&O  E&O  Correct as at 17 October 2018 08:08 All Each of E&O  E&O  E&O  Correct as at 17 October 2018 08:08 All Each of E&O  E&O  E&O  E&O  Correct as at 17 October 2018 08:08 All Each of E&O  E&O  E&O  E&O  E&O  E&O  E&O  E&O	Earth Terminal Capacity 2	4 x 1.5mm2			
Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E&O	Earth Terminal Capacity 3	3 x 2.5mm2			
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 206588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of E&O	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand			
Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or  European standard and the product information is  correct at the time of going to press.  All accessories are manufactured under an accredited  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM  E&O	Earth Terminal Capacity 5	1 x 6mm2			
Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Patents and Trademarks Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:08 AM E&O	Product Class 1	Must be earthed			
Maximum Installation Altitude  Standard/Approval  BS EN 60669-1  Patents and Trademarks  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&O	Ambient Operating Temperature	-5° to +40°C			
Standard/Approval  BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&O	Recommended Location	Internal Use Only			
Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  Correct as at 17 October 2018 08:08 AM E&O	Maximum Installation Altitude	2000m			
Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing  Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 17 October 2018 08:08 AM guarantee an exact colour match and shadings of	Standard/Approval	BS EN 60669-1			
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&Ol	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588			
Illustrations and diagrams are reproduced within  The limitations of reproduction and printing  Due to manufacturing processes we cannot  Solve to manufacturing processes we cannot  Guarantee an exact colour match and shadings of  E&Ol  E&Ol	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs		
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 17 October 2018 08:08 AM E&OE		

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio