Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio LPXSATIPB-ABW Linea-Perlina CFX Polished Brass Frame/Antique Brass Front 1 gang Isolated Satellite White Item Image Wiring Dimensions Hemilton Œ SATI Non-Isolated Satellite Sinale Terminal 92.0 Screen Cabl Under Clamp \odot Primary Range Linea-Perlina CFX Insert Type 1 gang Isolated Satellite Plate Finish Linea-Perlina CFX Polished Brass Frame/Antique Brass Insert Colour White EAN13 Barcode 5017504890674 Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm **Fixing Hole Centres** Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Must be earthed (ref BS7671 415.2.1) Product Class 1 -5° to +40°C Ambient Operating Temperature Internal Use Only Recommended Location Maximum Installation Altitude 2000m Isolated F-type outlet for Satellite or Cable TV installations where a DC signal back to the LNB unit on the satellite dish EuroFix Additional Notes NOT required. Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Patents and Trademarks Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 08:08 AM Illustrations and diagrams are reproduced within the limitations of reproduction and printing E&OE process and are not binding of certain finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimble SEC Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 +44 (0)1747 860088 F: +44 (0)1179 710414 info@hamilton-litestat.com www.hamilton-lite LUCKINS E: info@ w.hamilton-litestat.com

SL