

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **LPXSHSPB-PBW**

Linea-Perlina CFX Polished Brass Frame/Polished Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White

Primary Range Linea-Perima CEX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Linea-Perima CEX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Linea-Perima CEX Insert Type Plate Finish Linea-Perima CEX Vertical Polished Brass Frame-Polished Brass Insert Colour White EAN13 Barcode John Strong William Dimensions (Norminal) Double: Height = 151.0mm Width = 82.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 720.0mm Grid Fixing = CFX Clips Minimum Wall Box Depth Afrim Switched Poles None Current Rating John Switched Poles None Maximum Load Maximum None Terminal Capacity 1 S x 1mm2 Terminal Capacity 1 S x 1mm2 Terminal Capacity 1 S x 1mm2 Terminal Capacity 3 S x 25mm2 Terminal Capacity 4 S x 15mm2 Terminal Capacity 4 S x 15mm2 Earth Terminal Capacity 2 S x 15mm2 Earth Terminal Capacity 2 S x 15mm2 Earth Terminal Capacity 2 S x 15mm2 Earth Terminal Capacity 3 S x 25mm2 Earth Terminal Capacity 5 S x 15mm2 Earth Terminal Capacity 6 S x 15mm2 Earth Terminal Earth	Item Image	Wiring	Dimensions	
Insert Type	T. T.		SHS Shaver Dual Voltage Unswitched Socket (Vertical Mounted)  92.0  43.5  43.5	
Plate Finish   Linea-Perlina CFX Vertical Polished Brass Frame/Polished Brass	Primary Range	Linea-Perlina CFX		
Plate Finish   Linea-Perlina CFX Vertical Polished Brass Frame/Polished Brass		Shaver Dual Voltage Unswitched Socket (Vertically Mounted)		
EAN13 Barcode	Plate Finish			
Dimensions (Nominal)   Double: Height = 151.0mm   Width = 92.0mm   Depth = 4.0mm	Insert Colour	White		
Fixing Hole Centres	EAN13 Barcode	5017504870034		
Fixing Hole Centres	Dimensions (Nominal)			
Minimum Wall Box Depth         47mm           Switched Poles         None           Current Rating         20VA           Voltage         220/250V AC           Maximum Load         200/250V input; 115/230V 20VA output           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 -				
Current Rating         20VA           Voltage         220/250V AC           Maximum Load         200/250V input; 115/230V 20VA output           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573	Minimum Wall Box Depth			
Voltage         220/250V AC           Maximum Load         200/250V input; 115/230V 20VA output           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573	Switched Poles	None		
Maximum Load         200/250V input; 115/230V 20VA output           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573	Current Rating	20VA		
Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573	Voltage	220/250V AC		
IP Rating	Maximum Load	200/250V input; 115/230V 20VA output		
Contact Gap Minimum None  Terminal Capacity 1 5 x 1mm2  Terminal Capacity 2 4 x 1.5mm2  Terminal Capacity 3 3 x 2.5mm2  Terminal Capacity 4 2 x 4mm2 Multi-strand  Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 1 9 x 1mm2  Earth Terminal Capacity 2 6 x 1.5mm2  Earth Terminal Capacity 3 4 x 2.5mm2  Earth Terminal Capacity 3 4 x 2.5mm2  Earth Terminal Capacity 4 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Forduct Class 1 Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude  SEN 61558-2-5 - BS 4573	Mains Frequency	50Hz		
Terminal Capacity 1         5 x 1mm2           Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573	IP Rating	IP2XD		
Terminal Capacity 2         4 x 1.5mm2           Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573	Contact Gap Minimum	None		
Terminal Capacity 3         3 x 2.5mm2           Terminal Capacity 4         2 x 4mm2 Multi-strand           Terminal Capacity 5         1 x 6mm2           Earth Terminal Capacity 1         9 x 1mm2           Earth Terminal Capacity 2         6 x 1.5mm2           Earth Terminal Capacity 3         4 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4  2 x 4mm2 Multi-strand  Terminal Capacity 5  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  6 x 1.5mm2  Earth Terminal Capacity 3  4 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Sen Must be earthed  Standard/Approval  BS EN 61558-2-5 - BS 4573	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Internal Use Only  BS EN 61558-2-5 - BS 4573	Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5  1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval  BS EN 61558-2-5 - BS 4573	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Standard/Approval  A x 2.5mm2  1 x 6mm2  Must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  BS EN 61558-2-5 - BS 4573	Earth Terminal Capacity 1	9 x 1mm2		
Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  2 x 4mm2 Multi-strand  1 x 6mm2  Must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  Standard/Approval  BS EN 61558-2-5 - BS 4573	Earth Terminal Capacity 2	6 x 1.5mm2		
Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 61558-2-5 - BS 4573	Earth Terminal Capacity 3	4 x 2.5mm2		
Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 61558-2-5 - BS 4573	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 61558-2-5 - BS 4573	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location     Internal Use Only       Maximum Installation Altitude     2000m       Standard/Approval     BS EN 61558-2-5 - BS 4573	Product Class 1	Must be earthed		
Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS EN 61558-2-5 - BS 4573	Recommended Location	Internal Use Only		
	Maximum Installation Altitude	2000m		
Additional Notes Must be mounted vertically. Shuttered: Yes. Box Depth 47mm	Standard/Approval			



SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **LPXSHSPB-PBW**

Linea-Perlina CFX Polished Brass Frame/Polished Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 17 October 2018 08:08 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









