

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LPXSHSPB-SBB

Linea-Perlina CFX Polished Brass Frame/Satin Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black

| Linea-Perlina CFX Polished Brass Frame/Satin Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black | | | |
|---|---|--|--|
| Item Image | Wiring | Dimensions | |
| 830V F 112V | Newtral Land | LINEA PERLINA CFX SHS Shaver Dual Voltage Unswitched Socket (Vertical Mounted) 192.0 43.5 230V 115V | |
| Primary Range | Linea-Perlina CFX | | |
| Insert Type | Shaver Dual Voltage Unswitched Socket (Vertically Mounted) | | |
| Plate Finish | Linea-Perlina CFX Vertical Polished Brass Frame/Satin Brass | | |
| Insert Colour | Black | | |
| EAN13 Barcode | 5017504881030 | | |
| Dimensions (Nominal) | Double: Height = 151.0mm Width = 92.0mm Depth = 4.0mm | | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips | | |
| Minimum Wall Box Depth | 47mm | | |
| Switched Poles | None | | |
| Current Rating | 20VA | | |
| Voltage | 220/250V AC | | |
| Maximum Load | 200/250V input; 115/230V 20VA output | | |
| Mains Frequency | 50Hz | | |
| IP Rating | IP2XD | | |
| Contact Gap Minimum | None | | |
| Terminal Capacity 1 | 5 x 1mm2 | | |
| Terminal Capacity 2 | 4 x 1.5mm2 | | |
| Terminal Capacity 3 | 3 x 2.5mm2 | | |
| Terminal Capacity 4 | 2 x 4mm2 Multi-strand | | |
| Terminal Capacity 5 | 1 x 6mm2 | | |
| Earth Terminal Capacity 1 | 9 x 1mm2 | | |
| Earth Terminal Capacity 2 | 6 x 1.5mm2 | | |
| Earth Terminal Capacity 3 | 4 x 2.5mm2 | | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | | |
| Product Class 1 | Must be earthed | | |
| Ambient Operating Temperature | -5° to +40°C | | |
| Recommended Location | Internal Use Only | | |
| Maximum Installation Altitude | 2000m | | |
| Standard/Approval | BS EN 61558-2-5 - BS 4573 | | |
| Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm | | | |



SL

making connections beautifully

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio | | | |
|---|--|--|--|
| LPXSHSPB-SBB | | | |
| Linea-Perlina CFX Polished Brass Frame/Satin Brass Front Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Black | | | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 | | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 08:08 AM E&OE | |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









