

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LPXSPNRB-RBB

Linea-Perlina CFX Richmond Bronze Frame/Richmond Bronze Front 1 gang 13A Double Pole Fused Spur and Neon Richmond Bronze/Black

| European standard and the product information is Correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme. Therefore, we reserve the right to alter designs | Bronze/Black | | | |
|--|--|--|--|--|
| Primary Range Linea-Perlina CFX Insert Type 1 gang 13A Double Pole Fused Spur + Neon Linea-Perlina CFX Insert Type 1 gang 13A Double Pole Fused Spur + Neon Linea-Perlina CFX Linea-Perlina CFX Richmond Bronze Frame/Richmond Bronze EAN13 Barcode 5017504053389 Dimensions (Norninal) Single: Height = 92.0mm Wridth = 92.0mm Depth = 4.0mm Exhing Hole Centres 80x Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Current Rating 13 Amp Voltage 220250V AC Wakamum Load 13 Amp Mains Frequency 50Hz PRating 19PXD Contact Gap Minimum 3mm Terminal Capacity 1 7 Erminal Capacity 1 7 Erminal Capacity 1 7 Erminal Capacity 2 7 A firm? Writing Strand Terminal Capacity 2 7 Exh Imm2 Earth Terminal Capacity 1 8 S 1.5mm2 Earth Terminal Capacity 2 8 S 1.5mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 2 x 4mm2 Earth Terminal Capacity 4 2 x 4mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Earth Capacity 7 Earth Earth Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 2 Earth Terminal Capacity 1 E | Item Image | Wiring | Dimensions | |
| Insert Type | | Neutral Earth Live | SPN Switched Spur & Neon | |
| Plate Finish Linea-Perlina CFX Richmond Bronze Frame/Richmond Bronze Insert Colour Richmond Bronze/Black EAN13 Barcode Sot1760463389 Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Wall Box Depth Jamma Prequency IP Rating IP 2XD Contact Cag Minimum Smm Terminal Capacity 1 3 x 2.5mm2 Zar Minimum Wall Box Depth Jamma Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 4mm2 Multi-Strand Earth Terminal Capacity 3 2 x 4mm2 Multi-Strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5 for 4-40°C Recommended Location Maximum Installation Altitude Alignoches Issued Coloring to Juristic Propagation Linea is a Registered Trade Mark No 239865 CFX is a Registere | Primary Range | Linea-Perlina CFX | | |
| Insert Colour Richmond Bronze/Black EAN13 Barcode 5017504053369 Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Central Capacity 1 3 x 2.5mm2 Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 2 x 4mm2 Multi-strand Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5 | Insert Type | 1 gang 13A Double Pole Fused Spur + Neon | | |
| EAN13 Barcode 5017504053389 Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 5 x 4.5mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 x 7 x 7 x 7 x 7 x 7 x 7 x 7 x 7 x 7 x | Plate Finish | | | |
| Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 15 OHz IP Rating IP2XD Contact Gap Minimum 3mm Ferminal Capacity 1 1 x 6mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Forduct Class 1 Must be earthed Ambient Operating Temperature 1-5° to +40°C Recommended Location Internal Lise Only Maximum Installation Altitude BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European sta | Insert Colour | Richmond Bronze/Black | | |
| Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Simm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load Mains Frequency IP Rating Contact Gap Minimum 3mm Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 2 Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Ambient Operating Temperature Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS 1363-4 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. | EAN13 Barcode | 5017504053369 | | |
| Minimum Wall Box Depth Switched Poles Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 15 OHz IP Rating Contact Gap Minimum 3mm Terminal Capacity 1 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 In 6 mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity | Dimensions (Nominal) | Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm | | |
| Switched Poles Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand 1 x 6mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth | Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | | |
| Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5-5 to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SSZ is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. | Minimum Wall Box Depth | | | |
| Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 2 x 4mm2 Multi-strand Earth Terminal Capacity 6 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5-5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SSZ is a UK Registered Design Certificate No. 2066688 All products listed conform to current British or European standard and the product information is correct at the time of going to press. | Switched Poles | | | |
| Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 6 2 x 4mm2 Multi-strand Earth Terminal Capacity 6 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5-5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SSZ is a UK Registered Design Certificate No. 2066688 All products listed conform to current British or European standard and the product information is correct at the time of going to press. | Current Rating | | | |
| Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. | | | | |
| Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Fherefore, we reserve the right to alter designs. | | | | |
| IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1 mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of gioing to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to later designs. Therefore, we reserve the right to later designs. Therefore, we reserve the right to later designs. | Mains Frequency | | | |
| Terminal Capacity 1 Terminal Capacity 2 2 x 4mm2 Multi Strand 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tarth Terminal Capacity 5 Tarth Terminal Capacity 5 Tarth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Cap | | | | |
| Terminal Capacity 1 Terminal Capacity 2 2 x 4mm2 Multi Strand 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tarth Terminal Capacity 5 Tarth Terminal Capacity 5 Tarth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Cap | Contact Gap Minimum | 3mm | | |
| Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs | | | | |
| Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs | | 2 x 4mm2 Multi Strand | | |
| Earth Terminal Capacity 1 | | 1 x 6mm2 | | |
| Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature Arbient Operating Temperature Recommended Location Maximum Installation Altitude Standard/Approval Earth Terminal Capacity 5 Internal Use Only Maximum Installation Altitude Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs | | 6 x 1mm2 | | |
| Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designer. | | | | |
| Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Bs 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs Therefore, we reserve the right to alter designs | | | | |
| Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs | | 2 x 4mm2 Multi-strand | | |
| Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs | | 1 x 6mm2 | | |
| Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs | | Must be earthed | | |
| Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs | | -5° to +40°C | | |
| Maximum Installation Altitude 2000m Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs | | Internal Use Only | | |
| Standard/Approval BS 1363-4 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs | | 2000m | | |
| Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs | Standard/Approval | BS 1363-4 | | |
| European standard and the product information is Correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme. Therefore, we reserve the right to alter designs | | CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B | | |
| | European standard and the product information is | | | |
| | the limitations of reproduction and printing | guarantee an exact colour match and shadings of | Correct as at 17 October 2018 08:09 AM E&OE | |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1797 10414
E: info@hamilton-litestat.com www.hamilton-litestat.com
Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio