

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LPXSS1EB-EBB

	Linea-Perlina CFX Etrium Bronze Frame/Etrium Bronze Front 1 gang 13A Double Pole Switched Socket Etrium Bronze/Black			
Primary Range Insent Type Inse	Item Image	Wiring	Dimensions	
Insert Type		Neutral Earth Live	SS1 Switched Socket	
Plate Finish   Linea-Perlina CFX Etrium Bronze Frame/Etrium Bronze	Primary Range	Linea-Perlina CFX		
Insert Colour Etrium Bronze/Black EAN13 Barcode 5017504053406 Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Wallage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 1 4 x 2.5mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 5 2 x 6mm2 Multi-strand Earth Terminal Capacity 6 2 x 6mm2 Multi-strand Earth Terminal Capacity 7 1 x 10mm2 Earth Terminal Capacity 8 2 x 6mm2 Multi-strand Earth Terminal Capacity 9 1 x 10mm2 Earth Terminal Capacity 1 1 x 10mm2 Earth Terminal Capacity 9 1 x 10mm2 Earth Terminal Capacity 1	Insert Type	1 gang 13A Double Pole Switched Socket		
EAN13 Barcode 5017504053406  Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm  Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth 35mm  Switched Poles Double  Current Rating 13 Amp  Voltage 220/250V AC  Maximum Load 13 Amp  Walliam Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Freminal Capacity 1 4 x 2.5mm2  Terminal Capacity 1 4 x 2.5mm2  Terminal Capacity 2 3 x 4mm2  Terminal Capacity 3 2 x 6mm2 Multi-Strand  Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 1 4 x 2.5mm2  Earth Terminal Capacity 1 4 x 2.5mm2  Earth Terminal Capacity 1 1 x 10mm2  Earth Terminal Capacity 1 4 x 2.5mm2  Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand  Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 5 3 2 x 6mm2 Multi-Strand  Earth Terminal Capacity 6 3 2 x 6mm2 Multi-Strand  Earth Terminal Capacity 9 3 x 4mm2  Earth Terminal Capacity 9 3 x 4mm2  Earth Terminal Capacity 1 4 x 2.5mm2  Earth Terminal Capacity 9 3 x 4mm2  Earth Terminal Capacity 9 3 x 4mm2  Earth Terminal Capacity 9 5 x 4mm2  Earth Terminal Capacity 9 1 x 1 x 10mm2  Earth Terminal Capacity 9 1 x 1 x 10mm2  Earth Terminal Capacity 9 1 x 1 x 10mm2  Froduct Class 1 Must be earthed  Ambient Operating Temperature 5 to 440°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval Bis 18 x 1 x 10mm2	Plate Finish	Linea-Perlina CFX Etrium Bronze Frame/Etrium Bronze		
Dimensions (Nominal)  Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Switched Poles  Double  Current Rating  13 Amp  Voltage  220/250V AC  Maximum Load  13 Amp  Mains Frequency  19 Rating  19 PZXD  Contact Cap Minimum  Ferminal Capacity 1  4 x 2.5mm2  Terminal Capacity 1  4 x 2.5mm2  Terminal Capacity 2  3 x 4mm2  Ferminal Capacity 3  1 x 10mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  2 x 6mm2 Multi-Strand  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 10mm2  Earth Terminal Capacity 4  1 x 10mm2  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Termi	Insert Colour	Etrium Bronze/Black		
Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Double  Current Rating  13 Amp  Voltage  220/259V AC  Maximum Load  13 Amp  Mains Frequency  IP Rating  IP 2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  4 x 2.5mm2  Terminal Capacity 2  3 x 4mm2  Terminal Capacity 3  2 x 6mm2 Multi-Strand  Terminal Capacity 3  1 x 10mm2  Earth Terminal Capacity 1  4 x 2.5mm2  Earth Terminal Capacity 3  2 x 6mm2 Multi-strand  Terminal Capacity 3  2 x 6mm2 Multi-strand  An Department Capacity 3  3 x 4mm2  Earth Terminal Capacity 4  1 x 10mm2  Earth Terminal Capacity 3  2 x 6mm2 Multi-strand  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 10mm2  Froduct Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS 1363-2  Additional Notes  Lines is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  Therefore, we rever the right to alter designs and dimensions without prior motics.  BINISTIATION ACCORDANT SIGNED AND SIGNED AN	EAN13 Barcode	5017504053406		
Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz P Rating IPXD Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Terminal Capacity 4 1 x 10mm2 Terminal Capacity 4 1 x 10mm2 Terminal Capacity 4 1 x 10mm2 Terminal Capacity 5 2 x 6mm2 Multi-Strand Terminal Capacity 6 1 x 10mm2 Terminal Capacity 7 1 x 2 x 6mm2 Multi-Strand Terminal Capacity 8 1 x 10mm2 Terminal Capacity 9 1 x 10mm2 Term	Dimensions (Nominal)	Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm		
Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating 192XD Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 1 4 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Terminal Capacity 3 1 x 10mm2 Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 1 4 x 2.5mm2 Earth Terminal Capacity 1 4 x 2.5mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 3 1 x 10mm2 Earth Terminal Capacity 3 1 x 10mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 3 1 x 10mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5 to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2 Additional Notes Dual Earth: Yes Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of doing to press.  All products listed conform to current British or European standard and the product information is correct at the time of doing to press.  All products listed conform to current British or European standard and the product information is correct at the time of doing to press.  All products listed conform to current British or European standard and the product information is correct at the time of doing to press.  BEN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to aller designs and dimensions without prior notices.  Therefore, we reserve the right to aller designs and dimensions without prior notices.	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating 13 Amp  Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 4 x 2.5mm2  Terminal Capacity 2 3 x 4mm2  Terminal Capacity 3 2 x 6mm2 Multi-Strand  Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 1 4 x 2.5mm2  Earth Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 1 4 x 2.5mm2  Earth Terminal Capacity 3 2 x 6mm2 Multi-strand  Earth Terminal Capacity 3 1 x 4mm2  Earth Terminal Capacity 3 1 x 4mm2  Earth Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 5 2 x 6mm2 Multi-strand  Earth Terminal Capacity 6 1 x 10mm2  Earth Terminal Capacity 8 2 x 6mm2 Multi-strand  Earth Terminal Capacity 9 1 x 10mm2  Earth	Minimum Wall Box Depth	35mm		
Voltage   220/250V AC   Maximum Load   13 Amp   Mains Frequency   50Hz   FRating   FPZ/D     FRating   FPZ/D     FRATING   F	Switched Poles	Double		
Maximum Load  13 Amp  Mains Frequency  50Hz  IP Rating  IP PZXD  Contact Gap Minimum  Terminal Capacity 1  1	Current Rating	13 Amp		
Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 4.x 2.5mm2  Terminal Capacity 2 3.x 4mm2  Terminal Capacity 3 2.x 6mm2 Multi-Strand  Terminal Capacity 4 1.x 10mm2  Earth Terminal Capacity 1 4.x 2.5mm2  Earth Terminal Capacity 1 4.x 2.5mm2  Earth Terminal Capacity 1 4.x 2.5mm2  Earth Terminal Capacity 2 3.x 4mm2  Earth Terminal Capacity 2 3.x 4mm2  Earth Terminal Capacity 3 2.x 6mm2 Multi-strand  Earth Terminal Capacity 4 1.x 10mm2  Product Class 1 1.x 10mm2  All be earthed  Ambient Operating Temperature 5-5° to +40°C  Recommended Location 1.x 10mm2  Standard/Approval 1.x 10mm3  BS 1363-2  Dual Earth: Yes  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	Voltage	220/250V AC		
IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 4 x 2.5mm2  Terminal Capacity 2 3 x 4mm2  Terminal Capacity 3 2 x 6mm2 Multi-Strand  Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 1 4 x 2.5mm2  Earth Terminal Capacity 3 2 x 6mm2 Multi-strand  Earth Terminal Capacity 3 2 x 6mm2 Multi-strand  Earth Terminal Capacity 3 2 x 6mm2 Multi-strand  Earth Terminal Capacity 4 1 x 10mm2  Froduct Class 1 1 1 x 10mm2  Product Class 1 1 Must be earthed  Ambient Operating Temperature 5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2  Additional Notes Use are Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea is a Registered Trade Mark No 2398667 CFX is a Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of gioing to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  The refore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 17 October 2018 08:	Maximum Load	13 Amp		
Contact Gap Minimum  Terminal Capacity 1  4 x 2.5mm2  Terminal Capacity 2  3 x 4mm2  Terminal Capacity 3  2 x 6mm2 Multi-Strand  Terminal Capacity 4  1 x 10mm2  Earth Terminal Capacity 1  4 x 2.5mm2  Earth Terminal Capacity 2  3 x 4mm2  Earth Terminal Capacity 3  2 x 6mm2 Multi-strand  Earth Terminal Capacity 3  2 x 6mm2 Multi-strand  Earth Terminal Capacity 3  2 x 6mm2 Multi-strand  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 10mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  Additional Notes  Dual Earth: Yes  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But the product of the company to improve products as part of our development programme.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But the product of the company to improve products as part of our development programme.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But the product of the company to improve products as part of our development programme.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But the product of the company to improve products as part of our development programme.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But the product of the company to improve products as part of our development programme.  Correct at the time of going to press.	Mains Frequency	50Hz		
Terminal Capacity 1 4 x 2.5mm2  Terminal Capacity 2 3 x 4mm2  Terminal Capacity 3 2 x 6mm2 Multi-Strand  Terminal Capacity 4 1 x 10mm2  Earth Terminal Capacity 1 4 x 2.5mm2  Earth Terminal Capacity 2 3 x 4mm2  Earth Terminal Capacity 2 3 x 4mm2  Earth Terminal Capacity 3 2 x 6mm2 Multi-strand  Earth Terminal Capacity 3 1 x 10mm2  Earth Terminal Capacity 4 1 x 10mm2  Product Class 1 Must be earthed  Ambient Operating Temperature 5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2  Additional Notes Dual Earth: Yes  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398665  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as th To Cotober 2018 08:	IP Rating	IP2XD		
Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 1  Terminal Capacity 2  Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 6  Terminal Capacity 6  Terminal Capacity 6  Terminal Capacity 6  Terminal Capacity 7  Terminal Capacity 8  Terminal Capacity 8  Terminal Capacity 9  Terminal	Contact Gap Minimum	3mm		
Terminal Capacity 3  2 x 6mm2 Multi-Strand  1 x 10mm2  Earth Terminal Capacity 4  1 x 10mm2  Earth Terminal Capacity 1  2 x 6mm2 Multi-Strand  4 x 2.5mm2  Earth Terminal Capacity 2  3 x 4mm2  Earth Terminal Capacity 3  2 x 6mm2 Multi-strand  Earth Terminal Capacity 4  1 x 10mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 1363-2  Additional Notes  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Terminal Capacity 1	4 x 2.5mm2		
Terminal Capacity 4  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1 x 10mm2  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  Additional Notes  Dual Earth: Yes  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Terminal Capacity 2	3 x 4mm2		
Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Additional Notes  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Be N ISO 9001 : 2015 Quality Management System.  But M x 2.5mm2  Ax 4mm2  2 x 6mm2 Multi-strand  1 x 10mm2  Must be earthed  1 x 10mm2  Product Class 1  Must be earthed  1 x 10mm2  Product Class 1  Must be earthed  2 x 6mm2 Multi-strand  1 x 10mm2  Product Class 1  Must be earthed  2 x 6mm2 Multi-strand  1 x 10mm2  Product Class 1  All product No Product No CB 2383375B  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Terminal Capacity 3	2 x 6mm2 Multi-Strand		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Additional Notes  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  By All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  But to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Terminal Capacity 4	1 x 10mm2		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 1363-2  Additional Notes  Dual Earth: Yes  Linea is a Registered Trade Mark No 2398667  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  BIIIustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Earth Terminal Capacity 1	4 x 2.5mm2		
Earth Terminal Capacity 4  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 1363-2  Additional Notes  Dual Earth: Yes  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Earth Terminal Capacity 2	3 x 4mm2		
Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Additional Notes  Dual Earth: Yes  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Earth Terminal Capacity 3	2 x 6mm2 Multi-strand		
Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Additional Notes  Dual Earth: Yes  Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Earth Terminal Capacity 4	1 x 10mm2		
Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2  Additional Notes Dual Earth: Yes  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:		Must be earthed		
Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2  Additional Notes Dual Earth: Yes  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval  Additional Notes  Dual Earth: Yes  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:		Internal Use Only		
Additional Notes  Dual Earth: Yes  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Maximum Installation Altitude	2000m		
Additional Notes  Dual Earth: Yes  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Standard/Approval	BS 1363-2		
Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B  Linea-Perlina CFX SS2 is a UK Registered Design Certificate No. 2066588  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Additional Notes	Dual Earth: Yes		
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  Illustrations and diagrams are reproduced within  Due to manufacturing processes we cannot  Correct as at 17 October 2018 08:	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B		
	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
process and are not binding.  of certain finishes.	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 17 October 2018 08:09 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio