Hamilton

making connections beautifully

LPXT22PB-AB Linea-Perlina CFX Polished Brass Frame/Antique Brass Front 2 gang 20AX 2 Way Toggle Polished Brass Item Image Wiring Dimensions Image Image Image Image Image Image Image Image Image Image Image Image Image Image Image Image Image Image Image Image	Wining Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio				
Linea-Perlina CFX Polished Brass Frame/Antique Brass Front 2 gang 20AX 2 Way Toggle Polished Brass Item Image Wiring Dimensions Image Image Image Image Image Image Image Image Image Image Image Image Image Image Image Image Image					
Item Image Wiring Dimensions Image					
Image: Second			2 Way Toggle Polished Blass		
Pinnary Range Linea-Perina CFX Pinnary Range Linea-Perina CFX Insert Type 2 gang 20AX 2 Way Toggle Plate Finish Linea-Perina CFX Polished Brass Insert Type 2 gang 20AX 2 Way Toggle Plate Finish Linea-Perina CFX Polished Brass Insert Colour Polished Brass EANI 3 Barcode 5017504892265 Dimensions (Nominal) Single + Height = 92.0mm Width = 92.0mm Depth = 4.0mm Weight 303 GR Fining Hole Contres Box Fining = 60.3mm Grid Fixing = CFX Clips Minnum Wall Box Depth Single Current Rating 200250V AC Mains Fraquency 5044 Voltage 220250V AC Mains Fraquency 5044 P Rating 192XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x Imm2 Terminal Capacity 2 4 x Imm2 Terminal Capacity 3 2 x 2 Amm2 Terminal Capacity 4 5 x 1 Smm2 Terminal Capacity 5 1 x 6mm2 Eath Terminal Capacity 1 5 x 1 Smm2 Eath Terminal Capacity 3 3 x 2 Amm2 </th <th>Item Image</th> <th>Wiring</th> <th>Dimensions</th>	Item Image	Wiring	Dimensions		
Insert Type2 gang 20AX 2 Way TogglePlate FinishLinea-Perlina CFX Polished Brass Frame/Antique BrassInsert ColourPolished BrassEAN13 Barcode5017504892265Dimensions (Nominal)Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mmWeight303 GRFixing Hole CentresBox Fixing = 0.3mm Grid Fixing = CFX ClipsMinimur Wall Box Depth3smmSwitched PolesSingleCurrent Rating20AXVoltage220/250V ACMaximur Load20 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimur3mmTerminal Capacity 15 x 1mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 16 x 1mm2Earth Terminal Capacity 25 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 43 x 2.5mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 45 x 1.5mm2Earth		Image: specific specif	T22 2 Way Toggle		
Plate FinishLinea-Perina CFX Polished BrassInsert ColourPolished BrassEAN13 Barcode6017504892265Dimensions (Noninal)Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mmWeight303 GRFixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX ClipsMinimun Wall Box Depth35mmSwitched PolesSingleCurrent Rating20AXVoltage20/250V ACMains Frequency50HzIP RatingIP XDDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 33 x 2.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 45 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 45 x 1.5mm2Earth Terminal Capacity 45 x 1.5mm2Earth Terminal Capacity 45 x 1.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 45 x 1.5mm2Earth Terminal Capac	Primary Range	Linea-Perlina CFX			
Plate FinishLinea-Perina CFX Polished BrassInsert ColourPolished BrassEAN13 Barcode6017504892265Dimensions (Noninal)Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mmWeight303 GRFixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX ClipsMinimun Wall Box Depth35mmSwitched PolesSingleCurrent Rating20AXVoltage20/250V ACMains Frequency50HzIP RatingIP XDDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 33 x 2.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 45 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 45 x 1.5mm2Earth Terminal Capacity 45 x 1.5mm2Earth Terminal Capacity 45 x 1.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 45 x 1.5mm2Earth Terminal Capac	Insert Type	2 gang 20AX 2 Way Toggle			
Insert ColourPolished BrassEAN13 Barcode5017504892265Dimensions (Nominal)Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mmWeight303 GRFixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX ClipsMinimum Wall Box Depth35mmSwitched PolesSingleCurrent Rating20AXVoltage220/250V ACMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 24x 15mm2Terminal Capacity 22x 25mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 45x 15mm2Earth Terminal Capacity 45x 45mm2Earth Terminal Capacity 45x 45mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 45x 45mm2Earth Terminal Capacity 45x 45mm2Earth Terminal Capacity 45x 45mm2Earth Terminal Capacity 45x 45mm2Earth Terminal Capacity 45x 64mm2E	Plate Finish				
Dimensions (Nominal) Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm Weight 303 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 1 6 x 1mm2 Terminal Capacity 1 6 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 </td <td>Insert Colour</td> <td colspan="2"></td>	Insert Colour				
Weight 303 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 200/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Mu	EAN13 Barcode				
Weight 303 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX Voltage 200/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Mu		Single: Height = 92.0mm Width = 92.0mm Depth = 4.0mm			
Fixing Hole CentresBox Fixing = 60.3mmGrid Fixing = CFX ClipsMinimum Wall Box Depth35mmSwitched PolesSingleCurrent Rating20AXVoltage220/250V ACMaximum Load20 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 16 x 1mm2Terminal Capacity 15 x 1.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 16 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 55 x 1.5mm2Earth Terminal Capacity 51 x 6mm2Farth Terminal Capacity 55 x 1.5mm2Earth Terminal Capacity 51 x 6mm2Forduct Class 1Must be earthedAmbient Operating Temperature-5° to +40°C					
Minimum Wall Box Depth35mmSwitched PolesSingleCurrent Rating20AXVoltage220/250V ACMaximum Load20 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 51 x 6mm2Earth Terminal Capacity 16 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 55 x 1.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 55 x 1.5mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 75 x 1.5mm2Earth Terminal Capacity 51 x 6mm2Forduct Class 1Must be earthedAmbient Operating Temperature5° to +40°C					
Switched PolesSingleCurrent Rating20AXVoltage220/250V ACMaximum Load20 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 75 x 1.5mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 71 x 6mm2Forduct Class 1Must be earthedAmbient Operating Temperature <td></td> <td colspan="2"></td>					
Current Rating20AXVoltage220/250V ACMaximum Load20 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 75 x 1.5mm2Earth Terminal Capacity 61 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°C	Switched Poles				
Voltage220/250V ACMaximum Load20 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandFerminal Capacity 51 x 6mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 55 x 1.5mm2Earth Terminal Capacity 65 x 1.5mm2Earth Terminal Capacity 75 x 5.5mm2Earth Terminal Capacity 61 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°C	Current Rating				
Maximum Load20 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 16 x 1mm2Earth Terminal Capacity 25 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 51 x 5mm2Earth Terminal Capacity 51 x 5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°C					
Mains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 16 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Forduct Class 1Must be earthedAmbient Operating Temperature-5° to +40°C					
IP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 25 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°C	Mains Frequency				
Contact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 16 x 1mm2Earth Terminal Capacity 25 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature5° to +40°C					
Terminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 16 x 1mm2Earth Terminal Capacity 25 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandProduct Class 1Must be earthedAmbient Operating Temperature-5° to +40°C					
Terminal Capacity 24 x 1.5mm2Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 16 x 1mm2Earth Terminal Capacity 25 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandProduct Class 1Must be earthedAmbient Operating Temperature-5° to +40°C		5 x 1mm2			
Terminal Capacity 32 x 2.5mm2Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 16 x 1mm2Earth Terminal Capacity 25 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°C					
Terminal Capacity 42 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 16 x 1mm2Earth Terminal Capacity 25 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°C					
Terminal Capacity 51 x 6mm2Earth Terminal Capacity 16 x 1mm2Earth Terminal Capacity 25 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°C		2 x 4mm2 Multi-strand			
Earth Terminal Capacity 16 x 1mm2Earth Terminal Capacity 25 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°C					
Earth Terminal Capacity 25 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°C					
Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 42 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°C					
Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C					
Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C		2 x 4mm2 Multi-strand			
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C		1 x 6mm2			
		Must be earthed			
	Ambient Operating Temperature	-5° to +40°C			
Maximum Installation Altitude 2000m	Maximum Installation Altitude	2000m			
Standard/Approval BS EN 60669-1	Standard/Approval				

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LPXT22PB-AB

Linea-Perlina CFX Polished Brass Frame/Antique Brass Front 2 gang 20AX 2 Way Toggle Polished Brass

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GI Linea-Perlina CFX SS2 is a UK Registered Design Certificat	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 08:09 AM E&OE
	ad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84	Listed in Minimule LUCKINS Product selector

SL