




## LRX1X2VBC-BS

Linea-Rondo CFX Bright Chrome Frame/Bright Steel Front 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Bright Chrome

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|  |    |  <p style="text-align: center;"><b>Hamilton®</b><br/>LINEA RONDO CFX<br/>1X2V<br/>Inductive Leading Edge Push On-Off Rotary<br/>2 Way Switching Dimmer</p> |
| Primary Range   | Linea-Rondo CFX   |   |
| Insert Type   | 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer   |   |
| Plate Finish  | Linea-Rondo CFX Bright Chrome Frame/Bright Steel  |   |
| Insert Colour   | Bright Chrome   |   |
| EAN13 Barcode   | 5017504509118   |   |
| Dimensions (Nominal)  | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm  |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips   |   |
| Minimum Wall Box Depth  | 35mm  |   |
| Wattage   | 200VA (low voltage)   |   |
| Switched Poles  | Single  |   |
| Current Rating  | 0.8 Amp   |   |
| Voltage   | 220/250V AC   |   |
| Maximum Load  | 200VA (low voltage) Min Load 25VA   |   |
| Mains Frequency   | 50Hz  |   |
| IP Rating   | IP2XD   |   |
| Contact Gap Minimum   | None  |   |
| Terminal Capacity 1   | 2 x 1mm <sup>2</sup>  |   |
| Terminal Capacity 2   | 2 x 1.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>  |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand   |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>  |   |
| Product Class 1   | Face plate must be earthed  |   |
| Ambient Operating Temperature   | -5° to +40°C  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Standard/Approval   | BS EN 60669-1   |   |
| Additional Notes  | LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. |   |

## LRX1X2VBC-BS

### Linea-Rondo CFX Bright Chrome Frame/Bright Steel Front 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Bright Chrome

|   |   |   |
|---|---|---|
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428<br>Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.  | Correct as at 16 October 2018 04:00 PM<br>E&OE  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
T: +44 (0)1747 860088 F: +44 (0)1179 710414  
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **LUCKINS™**



CERT. No. FA11128