




LRX1XLEDITB100BC-PB

Linea-Rondo CFX Bright Chrome Frame/Polished Brass 1g 100W LED 2 Way Push On/Off Rotary Dimmer Bright Chrome

| Item Image | Wiring | Dimensions |
|---|---|---|
|  |  |  |
| Primary Range | Linea-Rondo CFX | |
| Insert Type | 1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer | |
| Plate Finish | Linea-Rondo CFX Bright Chrome Frame/Polished Brass | |
| Insert Colour | Bright Chrome | |
| EAN13 Barcode | 5017504084165 | |
| Dimensions (Nominal) | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Wattage | 5-100W (10 LED Lamps MAX) | |
| Switched Poles | Single | |
| Current Rating | 0.4A | |
| Voltage | 230V-240V | |
| Maximum Load | 5-100W (10 LED Lamps MAX) | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Terminal Capacity 1 | 2X1mm ² | |
| Terminal Capacity 2 | 2X1.5mm ² | |
| Earth Terminal Capacity 1 | 5X1mm ² | |
| Earth Terminal Capacity 2 | 4X1.5mm ² | |
| Earth Terminal Capacity 3 | 3X2.5mm ² | |
| Earth Terminal Capacity 4 | 1X4mm ² Multi-Strand | |
| Earth Terminal Capacity 5 | 1X6mm ² | |
| Product Class 1 | Face plate must be earthed | |
| Ambient Operating Temperature | -5°C to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-2-1 | |
| Additional Notes | Trailing Edge & Leading Edge Dimmer | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 04:00 PM E&OE |