




LRX2J12BC-SSB

Linea-Rondo CFX Bright Chrome Frame/Satin Steel Front 2 gang RJ12 Outlet - Unshielded Black

Item Image	Wiring	Dimensions																																				
	 <table border="1" data-bbox="808 646 966 730"> <thead> <tr> <th>Wire No.</th> <th>Color</th> <th>Wire No.</th> <th>Color</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>GREEN / White</td> <td>5</td> <td>YELLOW</td> </tr> <tr> <td>2</td> <td>ORANGE / White</td> <td>6</td> <td>GREEN</td> </tr> <tr> <td>3</td> <td>WHITE / Blue</td> <td>7</td> <td>RED</td> </tr> <tr> <td>4</td> <td>BLUE / White</td> <td>8</td> <td>BLACK</td> </tr> <tr> <td>5</td> <td>WHITE / Orange</td> <td>9</td> <td>WHITE</td> </tr> <tr> <td>6</td> <td>WHITE / Green</td> <td>10</td> <td>UNSHIELD</td> </tr> <tr> <td>7</td> <td>UNSHIELD</td> <td>11</td> <td>UNSHIELD</td> </tr> <tr> <td>8</td> <td>UNSHIELD</td> <td>12</td> <td>UNSHIELD</td> </tr> </tbody> </table>	Wire No.	Color	Wire No.	Color	1	GREEN / White	5	YELLOW	2	ORANGE / White	6	GREEN	3	WHITE / Blue	7	RED	4	BLUE / White	8	BLACK	5	WHITE / Orange	9	WHITE	6	WHITE / Green	10	UNSHIELD	7	UNSHIELD	11	UNSHIELD	8	UNSHIELD	12	UNSHIELD	
Wire No.	Color	Wire No.	Color																																			
1	GREEN / White	5	YELLOW																																			
2	ORANGE / White	6	GREEN																																			
3	WHITE / Blue	7	RED																																			
4	BLUE / White	8	BLACK																																			
5	WHITE / Orange	9	WHITE																																			
6	WHITE / Green	10	UNSHIELD																																			
7	UNSHIELD	11	UNSHIELD																																			
8	UNSHIELD	12	UNSHIELD																																			

Primary Range	Linea-Rondo CFX
Insert Type	2 gang RJ12 Outlet - Unshielded
Plate Finish	Linea-Rondo CFX Bright Chrome Frame/Satin Steel
Insert Colour	Black
EAN13 Barcode	5017504511562
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	N/A
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5 x 1mm ²
Earth Terminal Capacity 2	4 x 1.5mm ²
Earth Terminal Capacity 3	3 x 2.5mm ²
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand
Earth Terminal Capacity 5	1 x 6mm ²
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350

<p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p>	<p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>	<p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p>
<p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>	<p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p>	<p>Correct as at 16 October 2018 04:01 PM E&OE</p>

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM12138