




LRX2J12SN-SSB

Linea-Rondo CFX Satin Nickel Frame/Satin Steel Front 2 gang RJ12 Outlet - Unshielded Black

| Item Image | Wiring | Dimensions | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|------------|--------------|------------|--------------|---|-------|-------|------|---|--------|-------|--------|---|-------|------|-------|---|------|-------|-----|---|-------|--------|-------|---|-------|-------|-------|---|--------|--------|--------|---|--------|--------|--------|---|
|  |  <table border="1" data-bbox="808 646 967 730"> <thead> <tr> <th>Pin</th> <th>Color</th> <th>Wire Color</th> <th>Socket Color</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>GREEN</td> <td>White</td> <td>BLUE</td> </tr> <tr> <td>2</td> <td>ORANGE</td> <td>White</td> <td>YELLOW</td> </tr> <tr> <td>3</td> <td>WHITE</td> <td>Blue</td> <td>GREEN</td> </tr> <tr> <td>4</td> <td>BLUE</td> <td>White</td> <td>RED</td> </tr> <tr> <td>5</td> <td>WHITE</td> <td>Orange</td> <td>BLACK</td> </tr> <tr> <td>6</td> <td>WHITE</td> <td>Green</td> <td>WHITE</td> </tr> <tr> <td>7</td> <td>NO USE</td> <td>NO USE</td> <td>NO USE</td> </tr> <tr> <td>8</td> <td>NO USE</td> <td>NO USE</td> <td>NO USE</td> </tr> </tbody> </table> | Pin | Color | Wire Color | Socket Color | 1 | GREEN | White | BLUE | 2 | ORANGE | White | YELLOW | 3 | WHITE | Blue | GREEN | 4 | BLUE | White | RED | 5 | WHITE | Orange | BLACK | 6 | WHITE | Green | WHITE | 7 | NO USE | NO USE | NO USE | 8 | NO USE | NO USE | NO USE |  |
| Pin | Color | Wire Color | Socket Color | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | GREEN | White | BLUE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | ORANGE | White | YELLOW | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | WHITE | Blue | GREEN | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | BLUE | White | RED | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | WHITE | Orange | BLACK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | WHITE | Green | WHITE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 | NO USE | NO USE | NO USE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | NO USE | NO USE | NO USE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | |
|-------------------------------|---|--|
| Primary Range | Linea-Rondo CFX | |
| Insert Type | 2 gang RJ12 Outlet - Unshielded | |
| Plate Finish | Linea-Rondo CFX Satin Nickel Frame/Satin Steel | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017504521561 | |
| Dimensions (Nominal) | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | N/A | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 1 | 5 x 1mm ² | |
| Earth Terminal Capacity 2 | 4 x 1.5mm ² | |
| Earth Terminal Capacity 3 | 3 x 2.5mm ² | |
| Earth Terminal Capacity 4 | 1 x 4mm ² Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm ² | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| EuroFix Additional Notes | Can be used as either RJ11 (4 wires) or RJ12 (6 wires) | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 | |

| | | |
|---|---|---|
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 04:01 PM E&OE |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **LUCKINS**



CERT. No. FM12138