## Hamilton

### making connections beautifully

SL

3L	Thanking connor	CIONS Dedutifully						
	Wiring Accessories • Circuit Protection • Sm	hart Lighting Control & Multi-room Audio						
LRX2XTSPB-ABW								
Linea-Rondo CFX Polished Brass Frame/Antique Brass Front 2 gang Multi-Way Touch Slave Controller Polished Brass/White								
Item Image	Wiring	Dimensions						
		<b>I I </b>						
		Hemilton LINEA RONDO CFX						
	Multi- Way Wiring using Slave module(s)	2XTS Multi-WayTouch Slave Controller						
		91.5						
		91.5						
	MASTER MODULE SLAVE MODULE SLAVE MODULE ONLY ONE MASTER MODULE IS USED PER CIRCUIT.							
		H H						
Primary Range	Linea-Rondo CFX							
Insert Type	2 gang Multi-Way Touch Slave Controller							
Plate Finish	Linea-Rondo CFX Polished Brass Frame/Antique Brass							
Insert Colour	Polished Brass/White							
EAN13 Barcode	5017504420499							
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm							
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips							
Minimum Wall Box Depth	35mm							
Wattage	The same as Touch Master or Ceiling Dimmer							
Switched Poles	N/A							
Current Rating	The same as Touch Master or Ceiling Dimmer							
Voltage	220/250V AC							
Maximum Load	The same as Touch Master							
Mains Frequency	50Hz							
IP Rating	IP2XD							
Contact Gap Minimum	N/A							
Terminal Capacity 1	2 x 1mm2							
Terminal Capacity 2	2 x 1.5mm2							
Earth Terminal Capacity 1	5 x 1mm2							
Earth Terminal Capacity 2	4 x 1.5mm2							
Earth Terminal Capacity 3 Earth Terminal Capacity 4	3 x 2.5mm2							
Earth Terminal Capacity 4 Earth Terminal Capacity 5	1 x 4mm2 Multi-strand 1 x 6mm2							
Product Class 1								
Ambient Operating Temperature	Face plate must be earthed -5° to +40°C							
Recommended Location	-5° to +40°C Internal Use Only							
Maximum Installation Altitude								
Standard/Approval	BS EN 60669-2-1							
Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers								
Additional Notes should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers								

# Hamilton

#### making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

#### LRX2XTSPB-ABW

### Linea-Rondo CFX Polished Brass Frame/Antique Brass Front 2 gang Multi-Way Touch Slave Controller Polished Brass/White

Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	e product information is of going to press. S are reproduced within duction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of		It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04:02 PM E&OE		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.					
	dd, Brislington, Bristol, BS4 5NZ ce 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84		Listed in STrimble	ncs.Plus (ct the Intervention	

SL