

SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRX3XTMPB-SSW

Linea-Rondo CFX Polished Brass Frame/Satin Steel Front 3x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Polished Brass/White

	Tray Diministra i anoma Braes, Trince	vvay Diffifflets Polisfied Brass/vville			
Item Image	Wiring	Dimensions			
	Multi- Way Wiring using Slave module(s) Multi- Way Wiring using Slave module(s) Multi- Way Wiring using Slave module(s) Master Module Slave Modul	LINEA RONDO CFX 3XTM Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmer 40 172 1915			
Primary Range	Linea-Rondo CFX				
Insert Type	3 gang 250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmer				
Plate Finish	Linea-Rondo CFX Polished Brass Frame/Satin Steel				
Insert Colour	Polished Brass/White				
EAN13 Barcode	5017504440404				
Dimensions (Nominal)	Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm				
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips				
Minimum Wall Box Depth	35mm				
Wattage	250W Resistive 210VA Inductive				
Switched Poles	N/A				
Current Rating	1.1 Amps per gang				
Voltage	220/250V AC				
Maximum Load	250W Resistive per gang 210VA Inductive Min Load 25W/25VA				
Mains Frequency IP Rating	50Hz IP2XD				
Contact Gap Minimum	N/A				
Terminal Capacity 1	2 x 1mm2				
Terminal Capacity 2	2 x 1.5mm2				
Earth Terminal Capacity 1					
Earth Terminal Capacity 1 Earth Terminal Capacity 2	5 x 1mm2				
Earth Terminal Capacity 2 Earth Terminal Capacity 3	4 x 1.5mm2 3 x 2.5mm2				
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand				
Earth Terminal Capacity 5	1 x 4mm2 Multi-strand 1 x 6mm2				
Product Class 1	Face plate must be earthed				
Ambient Operating Temperature	-5° to +40°C				
Recommended Location	Internal Use Only				
Maximum Installation Altitude	2000m				
Standard/Approval	BS EN 60669-2-1				
Additional Notes	TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for dimming low voltage electronic halogen transformers it must be noted that the dimmer controls the primary side of the transformer. Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps-dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. When using mains voltage halogen load transformer - maximum rating is 210VA. NOTE: For multi-way switching a push to make retractive switch should be installed in the other positions. (Note:standard two way switches will not work with this product)				



SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRX3XTMPB-SSW

Linea-Rondo CFX Polished Brass Frame/Satin Steel Front 3x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Polished Brass/White

Way Billinolo Foliolica Brace, William			
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 16 October 2018 04:02 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









