## Hamilton

## making connections beautifully

SL

## Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LRX45SS1BK-BKB

Linea-Rondo CFX Black Nickel Frame/Black Nickel Front 45A Double Pole Rocker + Neon + 13A Switched Socket Red+Black Nickel/Black

| Nickel/Black  |   |  |
|---|---|--|
| Item Image  | Wiring  | Dimensions   |
|   |   | HEENDADOCFX<br>LINEA RANDOCFX<br>SSS1<br>Double Pole Red Rocker & Neon &<br>13A Switched Socket  |
| Primary Range   | Linea-Rondo CFX   |  |
| Insert Type   | 45A Double Pole Red Rocker + Neon + 13A Switched Socket   |  |
| Plate Finish  | Linea-Rondo CFX Black Nickel Frame/Black Nickel   |  |
| Insert Colour   | Red+Black Nickel/Black  |  |
| EAN13 Barcode   | 5017504532703   |  |
| Dimensions (Nominal)  | Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm   |  |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = CFX Clips  |  |
| Minimum Wall Box Depth  | 35mm  |  |
| Switched Poles  | Double  |  |
| Current Rating  | Switch 45 Amp Socket 13 Amp   |  |
| Voltage   | 220/250V AC   |  |
| Maximum Load  | Switch 45 Amp Socket 13   |  |
| Mains Frequency   | 50Hz  |  |
| IP Rating   | IP2XD   |  |
| Contact Gap Minimum   | 3mm   |  |
| Terminal Capacity 1   | 3 x 6mm2  |  |
| Terminal Capacity 2   | 2 x 10mm2   |  |
| Terminal Capacity 3   | 1 x 16mm2   |  |
| Earth Terminal Capacity 1   | 3 x 6mm2  |  |
| Earth Terminal Capacity 2   | 2 x 10mm2   |  |
| Earth Terminal Capacity 3   | 1 x 16mm2   |  |
| Product Class 1   | Must be earthed   |  |
| Ambient Operating Temperature   | -5° to +40°C  |  |
| Recommended Location  | Internal Use Only   |  |
| Maximum Installation Altitude   | 2000m   |  |
| Standard/Approval   | BS 4177   |  |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428<br>Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press.   | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within<br>the limitations of reproduction and printing<br>process and are not binding.  | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.   | Correct as at 16 October 2018 04:03 PM<br>E&OE   |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F<br>T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered<br>E: info@hamilton-litestat.com www.hamilton-litestat.com | Road, Brislington, Bristol, BS4 5NZ<br>Office 1 Rushmills, Bedford Road, Northampton NN4 7YB<br>in London No. 941624 VAT Registration No. 222 6607 84   | Listed in Trimble Collector Dis5Plus   |