Hamilton

making connections beautifully

SL

LIX45531PB-SSW Linea-Rondo CFX Polished Brass Frame/Satin Steel Front 45A Double Pole Rocker + Neon + 13A Switched Socket Red+Polished Brass/White Dimensions Item Image Wiring Dimensions Item Image Wiring Dimensions Item Image Wiring Dimensions Item Image Unes-Rondo CFX Dimensions International Control of the Control of		Wiring Accessories • Circuit Protection • Sr	nart Lighting Control & Multi-room Audio
Linea-Rondo CFX Polished Brass Frame/Satin Steel Front 45A Double Pole Rocker + Neon + 13A Switched Socket Rod+Polished Brass/White Dimensions Item Image Wiring Dimensions Iferent Image Use of the second sec			
Primary Range Linea-Rondo CFX Instant Type 46A Double Pool Rold Rolds r- Noon + 13A Switched Socket Primary Range Linea-Rondo CFX Instant Type 46A Double Pool Rolds r- Noon + 13A Switched Socket Parter Final Linea-Rondo CFX Rate Finan Double Courrent Rating Switch 45 Any Socket 13 Any Waithmut Load Switch 45 Any Socket 13 Any Waithmut Load Switch 45 Any Socket 13 Any Voltage 220/260V AC Mainter Meducatory Softwich 45 Any Read Financi Softwich 45 Any Read Roldsocky 3. Read Roldsocky 3. Read Roldsocky 3.x Binm2 Read	Linea-Rondo CFX Polished Brass I	Frame/Satin Steel Front 45A Double Pole Ro	cker + Neon + 13A Switched Socket
Finanzy Range Lnea-Rondo CFX Primary Range Lnea-Rondo CFX Primary Range Lnea-Rondo CFX Brasser Type 445 Double Pole Red Rocker + Neon + 13A Switched Socket Pilmary Range Lnea-Rondo CFX Brasser Type 445 Double Pole Red Rocker + Neon + 13A Switched Socket Pilmary Range Lnea-Rondo CFX Brasser Type 445 Double Pole Red Rocker + Neon + 13A Switched Socket Pilmary Range Lnea-Rondo CFX Brasser Type 601750/443702 Dimensions (Nominal) Double: Height = 6115.5mm Depth = 4.0mm Brasser Type Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 3fmrn Switch d 5 Amp Socket 13 Masser Forquency Golda Switch d 5 Amp Socket 13 Amp Wains Frequency Solda Gorared Rating Switch d 5 Amp Socket 13 Amp Wains Frequency Solda P Rating P220 Contact Gap Minimum 3mm Bram 2 Strimmal Capacity 1 Strimmal Capacity 1 3.8 mm2 Bram 7 Strimmal Capacity 2 Earth Terminal Capacity 2 2.x 10	Item Image	Wiring	Dimensions
Insert Type 45A Double Pole Red Rocker + Neon + 13A Switched Socket Plate Finish Linea-Rondo CFX Polished Brass Frame/Satin Steel Insert Colour Red+Polished Brass/White EAN13 Barcode 5017504443702 Dimensions (Nominal) Double: Height = 91.5mm Box Fixing = 120.6mm Gild Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double: Current Rating Switch 45 Amp Socket 13 Amp Voltage 220/250V AC Mains Frequency 50Hz Pattering IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 1 3 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5" to +40°C Recommended Location Internal Use Only Maixer Terminal Capacity 2 2 X 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5" to +40°C Recommended Location Internal Use Only Maixer Base and Trademarks Eleptered Trade Mark No 2398665 CFX is a Regi			LINEA RONDO CFX 45SS1 Double Pole Red Rocker & Neon &
Plate Finish Linea-Rondo CFX Polished Brass Frame/Satin Steel Insert Colour Red+Polished Brass/White EAN13 Barcode 5017504443702 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating Switch 45 Amp Socket 13 Amp Voltage 220/250V AC Maximum Load Switch 45 Amp Socket 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature 6* to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 <td>Primary Range</td> <td colspan="2">Linea-Rondo CFX</td>	Primary Range	Linea-Rondo CFX	
Insert Colour Red+Polished Brass/White EAN13 Barcode 5017504443702 Dimensions (Nominal) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating Switch 45 Amp Socket 13 Amp Voltage 220250V AC Maximum Load Switch 45 Amp Socket 13 Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 4 X 1000 Xust be earthed Ambient Operating Temperature 5 to 440°C Recommended Location Internal Use Only Maximun Installation Altfude 2000m Standard/Approval BS 4177 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark	Insert Type	45A Double Pole Red Rocker + Neon + 13A Switched Socket	
EAN13 Barcode 5017504443702 Dimensions (Nominal) Double: Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating Switch 45 Amp Socket 13 Amp Voltage 220/250V AC Maximum Load Switch 45 Amp Socket 13 Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature 5° to 140°C Recommended Location Internal Use Only Maximum Installation Altude 2000m Standard/Approval BS 4177 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 239866	Plate Finish	Linea-Rondo CFX Polished Brass Frame/Satin Steel	
Dimensions (Nominai) Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 20/250V AC Current Rating 20/250V AC Waximum Load Switch 45 Amp Socket 13 Amp Voltage 20/250V AC Maximum Load Switch 45 Amp Socket 13 Mains Frequency 50Hz PR Ating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 2 X 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks All accessories are manufactured under an accredited Stan Star(Souge) Star Star Star Star Star Star Star Star	Insert Colour	Red+Polished Brass/White	
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating Switch 45 Amp Socket 13 Amp Voltage 220/250V AC Maximum Load Switch 45 Amp Socket 13 Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 France 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5' to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Circle is a Registered Trade Mark No 2398665 CrX is a Registered Trade Mark No 2398665 CrX is a Registered Trade Mark No 2398665 CrX is a UK Registered Trade Ma	EAN13 Barcode	5017504443702	
Minimum Wall Box Depth 35mm Switched Poles Double Current Rating Switch 45 Amp Socket 13 Amp Voltage 220/250V AC Maximum Load Switch 45 Amp Socket 13 Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5' to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 All accessories are manufactured under an accredited as at of acdredipment programmer. Therefore, we reserve the right to alter designs and dimensions whould prior notice.	Dimensions (Nominal)	Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm	
Switched Poles Double Current Rating Switch 45 Amp Socket 13 Amp Voltage 220/250V AC Maximum Load Switch 45 Amp Socket 13 Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5' to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks CiPK is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 </td <td>Fixing Hole Centres</td> <td colspan="2">Box Fixing = 120.6mm Grid Fixing = CFX Clips</td>	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips	
Current Rating Switch 45 Amp Socket 13 Amp Voltage 220/250V AC Maximum Load Switch 45 Amp Socket 13 Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed contom to current	Minimum Wall Box Depth	35mm	
Voltage 220/250V AC Maximum Load Switch 45 Amp Socket 13 Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 It is the policy of the company to improve products BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products BS EN ISO 9001 :	Switched Poles	Double	
Voltage 220/250V AC Maximum Load Switch 45 Amp Socket 13 Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature -5' to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered	Current Rating	Switch 45 Amp Socket 13 Amp	
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 CFX is a Standard and the product information is correct at the time of going to press. It is the policy of the company to imp	-	220/250V AC	
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 CFX is a Standard and the product information is correct at the time of going to press. It is the policy of the company to imp	Maximum Load	Switch 45 Amp Socket 13	
IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Einea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd M	Mains Frequency		
Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambien Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398665 Maximum Installation of the products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All Stopping Carlificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European stan			
Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	<u> </u>	3mm	
Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to after designs and dimensions without prior notice.	-		
Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a UK Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		2 x 10mm2	
Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CTX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	1, 7		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the point or development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products and dimensions without prior notice.			
Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Standard/Approval BS 4177 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. and dimensions without prior notice.		Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428	
Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 16 October 2018. 04	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs
			Correct as at 16 October 2018 04:03 PM E&OE

1: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84