

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRX4XLEDITB100AB-AB

Linea-Rondo CFX Antique Brass Frame/Antique Brass 4g 100W LED 2 Way Push On/Off Rotary Dimmer Antique Brass

Item Image

Wiring

Dimensions Hamilton LINEA RONDO CFX LINEA RONDO CFX 4XLEDITB LEDITB100 2 Way Dimmer

Primary Range	Linea-Rondo CFX		
Insert Type	4 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer		
Plate Finish	Linea-Rondo CFX Antique Brass Frame/Antique Brass		
Insert Colour	Antique Brass		
EAN13 Barcode	5017504084806		
Dimensions (Nominal)	Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Wattage	5-70W Per Gang		
Switched Poles	Single	Single	
Current Rating	0.3A Per Gang		
Voltage	230V-240V		
Maximum Load	5-70W Per Gang		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Terminal Capacity 1	2X1mm²		
Terminal Capacity 2	2X1.5mm²		
Earth Terminal Capacity 1	5X1mm²		
Earth Terminal Capacity 2	4X1.5mm²		
Earth Terminal Capacity 3	3X2.5mm²		
Earth Terminal Capacity 4	1X4mm² Multi-Strand		
Earth Terminal Capacity 5	1X6mm²		
Product Class 1	Face plate muct be earthed		
Ambient Operating Temperature	-5°C to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1		
Additional Notes	Trailing Edge & Leading Edge Dimmer		
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 16 October 2018 04:03 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









