SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRX4XLEDITB100CB-CB

Plate Finish Linea-Rondo CFX Insert Colour Copper Bronze EAN13 Barcode 5017504084905 Dimensions (Nominal) Double: Height =	Wiring Dimensions Hemilton LINEA RONDO CFX 4XLEDITB LEDITB100 2 Way Dimmer LEDITB100 2 Way Dimmer To Dimensions A Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Copper Bronze Frame/Copper Bronze P1.5mm Width = 150.5mm Depth = 4.0mm Grid Fixing = CFX Clips
Insert Type	LEDITB100 2 Way Dimmer LEDITB100 2 Way Dimmer LEDITB100 2 Way Dimmer To Description of the state of the st
Insert Type	D Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Copper Bronze Frame/Copper Bronze = 91.5mm Width = 150.5mm Depth = 4.0mm
Insert Type	D Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer (Copper Bronze Frame/Copper Bronze = 91.5mm Width = 150.5mm Depth = 4.0mm
Plate Finish Linea-Rondo CFX Insert Colour Copper Bronze EAN13 Barcode 5017504084905 Dimensions (Nominal) Double: Height = Fixing Hole Centres Box Fixing = 120.6 Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 2 4X1.5mm²	Copper Bronze Frame/Copper Bronze = 91.5mm Width = 150.5mm Depth = 4.0mm
Insert Colour Copper Bronze EAN13 Barcode 5017504084905 Dimensions (Nominal) Double: Height = Fixing Hole Centres Box Fixing = 120.6 Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 2 4X1.5mm²	= 91.5mm Width = 150.5mm Depth = 4.0mm
EAN13 Barcode 5017504084905 Dimensions (Nominal) Double: Height = Fixing Hole Centres Box Fixing = 120.6 Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1.5mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 2 4X1.5mm²	•
Dimensions (Nominal) Double: Height = Fixing Hole Centres Box Fixing = 120.6 Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	•
Fixing Hole Centres Box Fixing = 120.6 Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	•
Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	6mm Grid Fixing = CFX Clips
Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	
Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	
Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	
Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	
Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	
Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	
IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	
Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	
Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	
Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm²	
Earth Terminal Capacity 2 4X1.5mm ²	
Earth Terminal Capacity 3 3X2.5mm ²	
Earth Terminal Capacity 4 1X4mm² Multi-Stra	and
Earth Terminal Capacity 5 1X6mm ²	
Product Class 1 Face plate muct be	e earthed
Ambient Operating Temperature -5°C to +40°C	
Recommended Location Internal Use Only	
Maximum Installation Altitude 2000m	
Standard/Approval BS EN 60669-2-1	
Additional Notes Trailing Edge & Le	eading Edge Dimmer
Patents and Trademarks CFX is a Registere	ered Trade Mark No 2398665 red Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 is a UK Registered Design Certificate No: R21=2106349 SS2=2106350
	es are manufactured under an accredited 3001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within Due to r the limitations of reproduction and printing guarantee process and are not binding.	manufacturing processes we cannot Correct as at 16 October 2018 04:03

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84









