




## LRX4XTSPB-ABB

Linea-Rondo CFX Polished Brass Frame/Antique Brass Front 4 gang Multi-Way Touch Slave Controller Polished Brass/Black

| Item Image  | Wiring   | Dimensions  |
|---|--|---|
|  |   |  <p style="text-align: center;"> <b>Hamilton®</b><br/>         LINEA RONDO CFX<br/>         4XTS<br/>         Multi-WayTouch Slave Controller     </p> |
| Primary Range   | Linea-Rondo CFX  |   |
| Insert Type   | 4 gang Multi-Way Touch Slave Controller  |   |
| Plate Finish  | Linea-Rondo CFX Polished Brass Frame/Antique Brass   |   |
| Insert Colour   | Polished Brass/Black   |   |
| EAN13 Barcode   | 5017504421724  |   |
| Dimensions (Nominal)  | Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm  |   |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = CFX Clips   |   |
| Minimum Wall Box Depth  | 35mm   |   |
| Wattage   | The same as Touch Master or Ceiling Dimmer   |   |
| Switched Poles  | N/A  |   |
| Current Rating  | The same as Touch Master or Ceiling Dimmer   |   |
| Voltage   | 220/250V AC  |   |
| Maximum Load  | The same as Touch Master   |   |
| Mains Frequency   | 50Hz   |   |
| IP Rating   | IP2XD  |   |
| Contact Gap Minimum   | N/A  |   |
| Terminal Capacity 1   | 2 x 1mm <sup>2</sup>   |   |
| Terminal Capacity 2   | 2 x 1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand  |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>   |   |
| Product Class 1   | Face plate must be earthed   |   |
| Ambient Operating Temperature   | -5° to +40°C   |   |
| Recommended Location  | Internal Use Only  |   |
| Maximum Installation Altitude   | 2000m  |   |
| Standard/Approval   | BS EN 60669-2-1  |   |
| Additional Notes  | Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers |   |

## LRX4XTSPB-ABB

### Linea-Rondo CFX Polished Brass Frame/Antique Brass Front 4 gang Multi-Way Touch Slave Controller Polished Brass/Black

|  |  |  |
|--|--|--|
| <p>Patents and Trademarks</p>  | <p>Linea is a Registered Trade Mark No 2398665<br/>                 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428<br/>                 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350</p> |  |
| <p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p> | <p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>   | <p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p> |
| <p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>                | <p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p>   | <p>Correct as at 16 October 2018 04:04 PM<br/>E&amp;OE</p>   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. 14912238