SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRX5320CB-CBB

Linea-Rondo CFX Copper Bronze Frame/Copper Bronze Front 2 gang 15A 110V AC American Unswitched Socket Black

| Item Image | Wiring 16A FG 1159 FG | Dimensions |
|---|---|--|
| | | Hamilton LINEA RONDO CFX 5320 Unswitched American Socket |
| | | 91.5 |
| Primary Range | Linea-Rondo CFX | |
| Insert Type | 2 gang 15A 110V AC American Unswitched Socket | |
| Plate Finish | Linea-Rondo CFX Copper Bronze Frame/Copper Bronze | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017504055851 | |
| Dimensions (Nominal) | Double: Height = 91.5mm Width = 150.5mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | None | |
| Current Rating | 15 Amp | |
| Voltage | 110V AC | |
| Maximum Load | 15 Amp | |
| Mains Frequency | 60Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | None | |
| Terminal Capacity 1 | 3 x 2.5mm2 | |
| Terminal Capacity 2 | 2 x 4mm2 | |
| Terminal Capacity 3 | 1 x 6mm2 Multi-strand | |
| Product Class 1 | Face plate must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN ISO 5733 IEC60884-1 | |
| Additional Notes | Shuttered :Yes | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 04:04 Pf E&O |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











