## Hamilto

SL

Primary Range

Insert Type

Plate Finish

Insert Colour

EAN13 Barcode

Switched Poles

Current Rating

Mains Frequency

**Terminal Capacity 1** 

Product Class 1

Standard/Approval

Voltage Maximum Load

IP Rating

**Fixing Hole Centres** 

## making connections beautifully Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio LRX6126BK-PBB Linea-Rondo CFX Black Nickel Frame/Polished Brass Front 1 gang 10/16A 220/250V AC German Unswitched Socket Black Item Image Wiring Dimensions Hemilton 6126 shed German Socket ô 0 Caraca Eart C Note: This socket in Non Polarised Linea-Rondo CFX 1 gang 10/16A 220/250V AC German Unswitched Socket Linea-Rondo CFX Black Nickel Frame/Polished Brass Black 5017504056193 Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Dimensions (Nominal) Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm None 10/16 Amp 220/250V AC 16 Amp 50Hz IP2XD Contact Gap Minimum None 3 x 2 5mm2 **Terminal Capacity 2** 3 x4mm2 **Terminal Capacity 3** 2 x 6mm2 Multi-Strand **Terminal Capacity 4** 1 x 10mm2 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Internal Use Only **Recommended Location** Maximum Installation Altitude 2000m BS EN ISO 5733 IEC60884-1

Additional Notes Shuttered:Yes Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Patents and Trademarks Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products European standard and the product information is as part of our development programme. correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot Correct as at 16 October 2018 04:04 PM Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. of certain finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimble SECA T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84 nton NN4 7YE LUCKINS

E&OE