




## LRX6126PB-BSW

Linea-Rondo CFX Polished Brass Frame/Bright Steel Front 1 gang 10/16A 220/250V AC German Unswitched Socket White

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|    |  <p>Note: This socket is Non Polarised</p>   |  <p>Hamilton<br/>LINEA RONDO CFX<br/>6126<br/>Unswitched German Socket</p>                   |
| Primary Range   | Linea-Rondo CFX   |   |
| Insert Type   | 1 gang 10/16A 220/250V AC German Unswitched Socket  |   |
| Plate Finish  | Linea-Rondo CFX Polished Brass Frame/Bright Steel   |   |
| Insert Colour   | White   |   |
| EAN13 Barcode   | 5017504056261   |   |
| Dimensions (Nominal)  | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm  |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips   |   |
| Minimum Wall Box Depth  | 47mm  |   |
| Switched Poles  | None  |   |
| Current Rating  | 10/16 Amp   |   |
| Voltage   | 220/250V AC   |   |
| Maximum Load  | 16 Amp  |   |
| Mains Frequency   | 50Hz  |   |
| IP Rating   | IP2XD   |   |
| Contact Gap Minimum   | None  |   |
| Terminal Capacity 1   | 3 x 2.5mm <sup>2</sup>  |   |
| Terminal Capacity 2   | 3 x 4mm <sup>2</sup>  |   |
| Terminal Capacity 3   | 2 x 6mm <sup>2</sup> Multi-Strand   |   |
| Terminal Capacity 4   | 1 x 10mm <sup>2</sup>   |   |
| Product Class 1   | Face plate must be earthed  |   |
| Ambient Operating Temperature   | -5° to +40°C  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Standard/Approval   | BS EN ISO 5733 IEC60884-1   |   |
| Additional Notes  | Shuttered:Yes   |   |
| Patents and Trademarks  | Linea is a Registered Trade Mark No 2398665<br>CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428<br>Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.   | Correct as at 16 October 2018 04:04 PM E&OE   |