





LRXDTRIDRB-RBB

Linea-Rondo CFX Richmond Bronze Frame/Richmond Bronze Front Non-Isolated TV+FM+SAT Triplexer 1in/3out (DAB Compatible) Black

| Item Image | Wiring | Dimensions |
|---|---|---|
|  |  <p>1. Undo the cable clamp screw. 2. Lift up the cover of the clamp, be careful not to displace the EMC gasket which is located on the cover. 3. Insert the conductor into the terminal slot which is located in the casing of the module. 4. Before closing the cover check to ensure that conductor, screening braid and cable are in the correct position as shown below. 5. Carefully close the cover of the module ensuring that the EMC gasket is not displaced or damaged. Then tighten the cable clamp screw.</p>  |  <p>Hamilton® LINEA RONDO CFX DTRID Non-Isolated TV/FM/Satellite1 Triplexer 1in/3out</p> |
| Primary Range | Linea-Rondo CFX | |
| Insert Type | Non-Isolated TV+FM+SAT Triplexer 1in/3out (DAB Compatible) | |
| Plate Finish | Linea-Rondo CFX Richmond Bronze Frame/Richmond Bronze | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017504057312 | |
| Dimensions (Nominal) | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | N/A | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 1 | 5 x 1mm ² | |
| Earth Terminal Capacity 2 | 4 x 1.5mm ² | |
| Earth Terminal Capacity 3 | 3 x 2.5mm ² | |
| Earth Terminal Capacity 4 | 1 x 4mm ² Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm ² | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| EuroFix Additional Notes | Triplexer for use with combined TV FM and Satellite Signal (DAB compatible) | |
| Frequencies 1 | TV=5-68 MHz 125-860 MHz | |
| Frequencies 2 | FM=88-108 MHz | |
| Frequencies 3 | SAT DC=950-2200 MHz | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. | Correct as at 16 October 2018 04:05 PM E&OE |