SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRXDTVFBC-BSB

Linea-Rondo CFX Bright Chrome Frame/Bright Steel Front 1 gang Non-Isolated TV (female) Black

Item Image Wiring **Dimensions** Hamilton DTVF Non-Isolated TV (female) EMC Gasket Conductor Terminal Screw Correct position of 0 conductor, screening braid and cable Primary Range Linea-Rondo CFX Insert Type 1 gang Non-Isolated TV (female) (DAB Compatible) Plate Finish Linea-Rondo CFX Bright Chrome Frame/Bright Steel Insert Colour Black EAN13 Barcode 5017504501532 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Must be earthed (ref BS7671 415.2.1) Product Class 1 -5° to +40°C **Ambient Operating Temperature** Recommended Location Internal Use Only Maximum Installation Altitude 2000m EuroFix Additional Notes TV Outlet (IEC 169-2 Female Socket) Usually used for FM (DAB) outlet Frequencies 1 TV DC=5-2200 MHz Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Patents and Trademarks Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products BS EN ISO 9001 : 2015 Quality Management System European standard and the product information is as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1179 7010414
Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Einfo@hamilton-litestat.com www.hamilton-litestat.com www.ham

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing

process and are not binding.











Correct as at 16 October 2018 04:06 PM

