Hamilton

making connections beautifully

| | Wiring Accessories • Circuit Protection • Sn | mart Lighting Control & Multi-room Audio |
|--|---|--|
| | LRXDTVMSN-BSB | |
| Linea-Rondo CEX Sati | n Nickel Frame/Bright Steel Front 1 gang Non | -Isolated TV (Male) Black |
| | | |
| Item Image | Wiring | Dimensions |
| | EMC Gasket Conductor Terminal Screw Correct position of conductor, screening braid and cable | LINEA RONDO CFX DTM Non-Isolated TV (male) |
| Primary Range | Linea-Rondo CFX | |
| Insert Type | 1 gang Non-Isolated TV (Male) (DAB Compatible) | |
| Plate Finish | Linea-Rondo CFX Satin Nickel Frame/Bright Steel | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017504541514 | |
| Dimensions (Nominal) | Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | N/A | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| EuroFix Additional Notes | TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet | |
| Frequencies 1 | FM DC=5-2200 MHz | |
| Patents and Trademarks | Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 16 October 2018 04:06 P E&C |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered | Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84 | Listed in Stringer product selector DSSPUs CRI. No. IM1128 |