SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRXFNAB-SBR

Insert Type	Linea-Rondo CFX Antique Brass Frame/Satin Brass Front 1 gang 13A Fuse with Neon Halo Antique Brass/Red			
Firmary Range Linea-Rondo CFX Intent Type 1 gang 13A Fuse with Red Neon Hato Parties First Linea-Rondo CFA Antique Brass Frame/Satin Brass Intent Cobort EAN13 Barcode Antique Brass-Red SAN13 Barcode Sontres-Rondo	Item Image	Wiring		
Insert Type I gang 13A Fuse with Red Neon Halo Place Finish Linea-Rondo CFX Antique Brass Frame/Satin Brass Insert Colour Antique Brass Frame/Satin Brass Remain Satrode S017504472061 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Whichman Wall Box Depth Somm Whithin Wall Box Depth Whithin Wall Box Depth Somm Whithin Wall Box Depth Whithin Wall Box	FUSE	13A 250V-BS5733	FN Fuse with Red Neon Halo	
Plate Finish Linear-Rondo CFX Antique Brass Frame/Satin Brass Insert Colour Antique Brass Red EAN13 Barcode 5017504472061 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Current Rating 13 Amp Current Rating 13 Amp 14 Amp 15 Amp 15 Amp 16 Parking = CFX Clips Minimum Load 13 Amp 18 Amp Cortact Gap Minimum Load 13 Amp Pavo Cortact Gap Minimum 3mm Ferminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 1 6 x 1 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 4 2 x 4 mm2 Multi-strand Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 4.5mm2 Earth Terminal Capacity 7 5 x 4.5mm2 Earth Terminal Capacity 8 5 x 5.7sm 3 with Fuselink to BS1362 Linea Secondor Off x is at UR Registered Departed Mark No 2398667 EX is Registered Trade Mark No 2398667 EX is Registered Trade Mark No 2398667 Patent No. R21-2106349 SS2-2106350 Linea Secondor Off x is at UR Registered Departed Mark No 2398667 Patent No. R21-2106349 SS2-2106350 Linea Secondor Off x is at UR Registered Departed under an accredition and dimensions without prior notice. EX is the policy of the convergence in an accredition of the product information is correct at the time of gray to prioring processes and are not bringing. Due to manufacturing process	Primary Range	Linea-Rondo CFX		
Insent Colour Antique Brass/Red 5017504472061 Singre-Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Ourrent Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP P2XD Contact Gap Minimum Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand 1 x 6mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5 to 440°C Recommended Location Internal Use Only Maximum Installation Altitude Bas S733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No. 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No. 2398667 Patent No. CB 29393758 Community Trid Mark No. 00290428 Linea is a Registered Trade Mark No. 2398667 Patent No. CB	Insert Type	1 gang 13A Fuse with Red Neon Halo		
EAN13 Barcode 5017504472061 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fining Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load All Products (Base 1 American) All products listed conform to current Pirish or Europe and Maximum Installation Altitude All products listed conform to current Pirish or Europe Six 1 As Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398666 CPX is a Registered Trade Mark No 2398666 CPX is a Registered Trade Mark No 2398666 CPX is a Registered Trade Mark No 2398667 CPX is a Registered Trade Mark No 2398666 CPX is a Registered Trade Mark No 2398667 CPX is a R	Plate Finish			
EAN13 Barcode 5017504472061 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fining Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load All Products (Base 1 American) All products listed conform to current Pirish or Europe and Maximum Installation Altitude All products listed conform to current Pirish or Europe Six 1 As Registered Trade Mark No 2398665 CPX is a Registered Trade Mark No 2398666 CPX is a Registered Trade Mark No 2398666 CPX is a Registered Trade Mark No 2398666 CPX is a Registered Trade Mark No 2398667 CPX is a Registered Trade Mark No 2398666 CPX is a Registered Trade Mark No 2398667 CPX is a R	Insert Colour	Antique Brass/Red		
Box Fixing = 60.3mm Grid Fixing = CFX Clips	EAN13 Barcode	5017504472061		
Minimum Wall Box Depth Switched Poles None Current Rating Voltage 220/250V AC Maximum Load 13 Amp Wall Serquency 15 Pating P	Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm		
Switched Poles Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP SNHz IP Rating IP SNHz Contact Gap Minimum Terminal Capacity 1 3 x 2.5mm2 1 x 6mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Termina	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating Voltage 220/250V AC Maximum Load 13 Amp Soltz P Rating P2XD Contact Gap Minimum 3mm 1eminal Capacity 1 3 x 2.5mm2 Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 3 5 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature 5-5 to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Earth Say 3 x 1 the Use Only Maximum Installation Altitude 2000m Altimate Say 3 x 1 the Use Only All accessories are manufactured under an accended Explanation and printing or correct at the time of going to press. All products listed conform to current British or European standard and the product Information is correct at the time of going to press. All accessories are manufactured under an accended BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of correct as at 16 October 2018 04.05 PM ESCO	Minimum Wall Box Depth	35mm		
Voltage 220/250 V AC Maximum Load 13 Amp Mains Frequency 50Hz PRating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 8 2 x 4mm2 Multi-strand Earth Terminal Capacity 9 2 5 x 1.5mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 9 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5-5° to +40°C Maximum Installation Altitude 2000m Standard/Approval B5 5733 with Fuselink to B51362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 Patent No. 621=22106349 \$S2=2106350 Linea is a Registered Trade Mark No 2398665 Patent No. 621=22106349 \$S2=2106350 European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All and the product information is correct at the time of going to press. All and the product information is correct at the time of going to press. All and the product information is correct at the time of going to press. All and the product information is correct at the time of going to press. All and the product information is correct at the time of going to press. All and the product information is correct at the time of going to press. BESOE NISO 9001 : 2015 Quality Management System. Public to manufacturing processes we cannot guarantee an exact colour match and shadings of correct as at 16 October 2018 04:05 PM. EXCE	Switched Poles	None		
Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum Terminal Capacity 1 3x 2.5mm2 Terminal Capacity 2 2x 4mm2 Multi Strand Terminal Capacity 3 1x 6mm2 Earth Terminal Capacity 1 5x 1.5mm2 Earth Terminal Capacity 2 5x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 4 2x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Froduct Class 1 Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398667 CFX is a Registered Trade Mark No 239867 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is Correct at the time of digning to press. All products listed conform to current British or European standard and the product information is Correct at the time of digning to press. All products listed conform to current British or European standard and the product information is Correct at the time of digning to press. All products listed conform to current British or European standard and the product information is Correct at the time of digning to press. All products listed conform to current British or European standard and the product information is Correct at the time of digning to press. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Current Rating	13 Amp		
Mains Frequency Annual Sepacity 1 Freminal Capacity 2 Freminal Capacity 2 Freminal Capacity 3 Farth Terminal Capacity 1 Farth Terminal Capacity 3 Farth Terminal Capacity 4 Farth Terminal Capacity 4 Farth Terminal Capacity 5 Farth Terminal Capacity 5 Farth Terminal Capacity 6 Farth Terminal Capacity 8 Farth Terminal Capacity 9 Far	Voltage	220/250V AC		
P Rating Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 2 x 4mm2 Multi Strand Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1 mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval All products listed conform to current British or European standard and the product information is CPX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea is a Registered Trade Mark No 2398667 Patent No. R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is CPX is a Registered Trade Mark No 2398667 Patent No. R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is CPX is a Registered Trade Mark No 2398667 Patent No. R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is CPX is a Registered Trade Mark No 2398667 Patent No. R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certificates not Correct as at 16 October 2018 04:06 PM E&OE process and are not britindly.	Maximum Load	13 Amp		
Contact Gap Minimum Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo OFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product Information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Bustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not brinding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certificate No: Correct as at 16 October 2018 04.06 PM EACE process and are not brinding.	Mains Frequency	50Hz		
Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 3° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited as prevent the right to alter designs and dimensions without prior notice. BUS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finisher or certain and are not binding.	IP Rating	IP2XD		
Terminal Capacity 2 2 x 4mm2 Multi Strand 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:06 PM EACE	Contact Gap Minimum	3mm		
Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Amm2 Earth Terminal Capacity 5 Amm2 Earth Terminal Capacity 5 Internal Use Conly Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Due to manufacturing processes we cannot and dimensions without prior notice. EXCORDED ALL IS A TERMINAL AND ALL IS A TERMINA	Terminal Capacity 1	3 x 2.5mm2		
Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Patents and Trademarks CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106349 SS2=2106349 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 16 October 2018 04:06 PM E&OE	Terminal Capacity 2	2 x 4mm2 Multi Strand		
Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 16 October 2018 04:06 PM E&OE	Terminal Capacity 3	1 x 6mm2	1 x 6mm2	
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a Unical-Rondo CF	Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Bs 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 16 October 2018 04:06 PM E&OE	Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 16 October 2018 04:06 PM E&OE	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 16 October 2018 04:06 PM E&OE	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks Linea is a Registered Trade Mark No 2398667 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Correct as at 16 October 2018 04:06 PM the limitations of reproduction and printing processes and are not binding.	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not binding. Correct as at 16 October 2018 04:06 PM E&OE of certain finishes.	Product Class 1	Must be earthed		
Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS 5733 with Fuselink to BS1362 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Recommended Location	Internal Use Only		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 16 October 2018 04:06 PM E&OE	Maximum Installation Altitude	2000m		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not binding. CFX is a Registered Trade Mark No. 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04:06 PM E&OE of certain finishes.	Standard/Approval	BS 5733 with Fuselink to BS1362		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 16 October 2018 04:06 PM E&OE	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428		
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of of certain finishes.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing process and are not binding.	guarantee an exact colour match and shadings of of certain finishes.	E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









