SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **LRXFNPB-SBR**

| Item Image    Dimensions   Hamilton   Lieu Androom   Lieu Androom  | Linea-Rondo CFX Polished Brass Frame/Satin Brass Front 1 gang 13A Fuse with Neon Halo Polished Brass/Red |   |  |  |
|--|--|---|--|--|
| Primary Range Linea-Rondo CFX Insent Type 1 gang 13A Fuse with Red Neon Halo Linea-Rondo CFX Insent Type 1 gang 13A Fuse with Red Neon Halo Linea-Rondo CFX Polished Brass Frame/Satin Brass Insent Colour Polished Brass-Red EAN13 Barcode 501750412007 EAN13 Barcode 501750412007 EAN13 Barcode 501750412007 EAN13 Barcode Mindrum Wall Box Depth 30mm Swetched Poles Box Fixing = 80.3mm Grid Fixing = CFX Clips Mindrum Wall Box Depth 30mm Swetched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load Mains Firequency 14 Amp PXD Contact Gap Minimum Smm PPXD Contact Gap Minimum Smm PPXD Terminal Capacity 1 Farminal Capacity 1 Farminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Ear | Item Image   | Wiring  |  |  |
| Insert Type  | Ausa   | 13A 250V~ BS5733  | FN Fuse with Red Neon Halo   |  |
| Plate Finish   Linea-Rondo CFX Polished Brass Frame/Satin Brass  | Primary Range  | Linea-Rondo CFX   |  |  |
| Insert Colour Polished Brass/Red S017504412067 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum IP2XD Contact Gap Minimum IP2XD Contact Gapa Minimum IP2XD Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 8 x 6mm2 Earth Terminal Capacity 8 8 x 7 x 6mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth | Insert Type  | 1 gang 13A Fuse with Red Neon Halo  |  |  |
| EAN13 Barcode 5017594412067  Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm  Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth 35mm  Switched Poles None  Current Rating 13 Amp  Voltage 202/560 V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Cap Minimum 3mm  Terminal Capacity 1 3 x 2.5mm2  Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Earth Terminal Capacity 7 2 x 4mm2 Multi-strand  Earth Terminal Capacity 8 3 x 2.5mm2  Earth Terminal Capacity 9 5 x 1.5mm2  Earth Terminal Capa | Plate Finish   | Linea-Rondo CFX Polished Brass Frame/Satin Brass  |  |  |
| Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 19 Rating Pexko Contact Gap Minimum Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 2 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 4 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 1 Earth Terminal Capacity 6  | Insert Colour  | Polished Brass/Red  |  |  |
| Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Switched Poles  None  Current Rating  13 Amp  Voltage  220/250V AC  Maximum Load  13 Amp  Walins Frequency  IP Rating  IP2XD  Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 1  1 x 6mm2  Terminal Capacity 3  2 x 4mm2 Multi Strand  Terminal Capacity 3  1 x 6mm2  Earth Terminal Capacity 1  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 5  1 x 6mm2  Froduct Class 1  Ambient Operating Temperature  5 **To +40**C  Recommended Location  Maximum Installation Altitude  2000m  Bard Trademarks  All products listed conform to current British or European standard and the product Information is correct at the time of going to press.  Pale policy Fix is an accredited BS ENISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and differences war and differences war for product capacity to the company to improve products as part of understones war for the regions and differences when the region capacity in prove products as part of understones war for the regions and differences when the right to alter designs and differences with response and differences when the right to alter designs and differences with the right to alter designs and differences with the right to alter designs and differences when the right to alter designs and differences whene the right to alter designs and differences when the right to al | EAN13 Barcode  | 5017504412067   |  |  |
| Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth  35mm  Switched Poles  None  Current Rating  13 Amp  Voltage  220/250V AC  Maximum Load  13 Amp  Walins Frequency  IP Rating  IP2XD  Contact Gap Minimum  Terminal Capacity 1  Terminal Capacity 1  2 x 4mm2 Multi Strand  Terminal Capacity 3  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Exh Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 6  Earth Terminal Capacity 7  Earth Terminal Capacity 8  Earth Terminal Capacity 9  Earth Terminal Capacity 1  Earth Terminal Capacity 9  Earth Te | Dimensions (Nominal)   |   |  |  |
| Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/250V AC  Maximum Load 13 Amp Mains Frequency 50Hz IP Rating P2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand Terminal Capacity 2 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 5 x 1.5mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 1 5 |  |   |  |  |
| Current Rating 13 Amp  Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3 x 2.5mm2  Terminal Capacity 2 2 x 4mm2 Multi Strand  Terminal Capacity 3 1 x 6mm2  Earth Terminal Capacity 1 6 x 1 mm2  Earth Terminal Capacity 1 6 x 1 mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 6 1 x 6mm2  Forduct Class 1 Must be earthed  Ambient Operating Temperature 5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 5733 with Fuselink to BS1362  Patents and Trademarks Listed conform to current British or European standard and the product Information is correct at the time of going to press.   | Minimum Wall Box Depth   |   |  |  |
| Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating 19   | Switched Poles   |   |  |  |
| Maximum Load  13 Amp  Mains Frequency  50Hz  IP Rating  IP ZXD  Contact Gap Minimum  3mm  Terminal Capacity 1  3 x 2.5mm2  Terminal Capacity 2  2 x 4mm2 Multi Strand  1 x 6mm2  Earth Terminal Capacity 3  1 x 6mm2  Earth Terminal Capacity 3  5 x 1.5mm2  Earth Terminal Capacity 3  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  5 x 1.5mm2  Earth Terminal Capacity 3  2 x 4mm2 Multi-strand  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  B S 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.   | Current Rating   |   |  |  |
| Mains Frequency  Frating  IP Rating  IP2XD  Contact Gap Minimum  3mm  3 x 2.5mm2  Terminal Capacity 1  3 x 2.5mm2  Terminal Capacity 2  2 x 4mm2 Multi Strand  Terminal Capacity 3  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Froduct Class 1  Ambient Operating Temperature  Abient Operating Temperature  Best 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398665  CPX is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.   | Voltage  | · ·   |  |  |
| IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3 x 2.5mm2  Terminal Capacity 2 2 x 4mm2 Multi Strand  Terminal Capacity 3 1 x 6mm2  Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Forduct Class 1 Must be earthed  Ambient Operating Temperature 5 to 4-40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.  | Maximum Load   | 13 Amp  |  |  |
| Contact Gap Minimum  Terminal Capacity 1  3 x 2.5mm2  Terminal Capacity 2  2 x 4mm2 Multi Strand  Terminal Capacity 3  1 x 6mm2  Earth Terminal Capacity 1  5 x 1.5mm2  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  5 x 1.5mm2  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Maximum Installation Altitude  2000m  Standard/Approval  Bis 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398667  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited Bis the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.   | Mains Frequency  | 50Hz  |  |  |
| Terminal Capacity 1 3 x 2.5mm2  Terminal Capacity 2 2 x 4mm2 Multi Strand  Terminal Capacity 3 1 x 6mm2  Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature 5-5 to +40 °C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 5733 with Fuselink to BS1362  Patents and Trademarks Linea is a Registered Trade Mark No 2398665  CPX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.   | IP Rating  | IP2XD   |  |  |
| Terminal Capacity 2  Terminal Capacity 3  Earth Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Therminal Capacity 5  Therminal Capacity 5  Therminal Capacity 5  Therminal Capacity 6  Earth Terminal Capacity 6  Earth Terminal Capacity 6  Therminal Capacity 8  Therminal Capacity 8  Earth Terminal Capacity 8  Therminal Capacity 9  Therminal Cap | Contact Gap Minimum  | 3mm   |  |  |
| Terminal Capacity 3  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  Ambient Operating Temperature  Ambient Operating Temperature  Fecommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.   | Terminal Capacity 1  | 3 x 2.5mm2  |  |  |
| Earth Terminal Capacity 1  | Terminal Capacity 2  | 2 x 4mm2 Multi Strand   |  |  |
| Earth Terminal Capacity 2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Maximum Installation Altitude  2000m  Standard/Approval  Bs 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667  CFX is a Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.   | Terminal Capacity 3  | 1 x 6mm2  |  |  |
| Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Maximum Installation Altitude  2000m  Standard/Approval  Bs 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  | Earth Terminal Capacity 1  | 6 x 1mm2  |  |  |
| Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Earth Terminal Capacity 5  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.   | Earth Terminal Capacity 2  | 5 x 1.5mm2  |  |  |
| Earth Terminal Capacity 5  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.   | Earth Terminal Capacity 3  | 3 x 2.5mm2  |  |  |
| Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  | Earth Terminal Capacity 4  | 2 x 4mm2 Multi-strand   |  |  |
| Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.   | Earth Terminal Capacity 5  | 1 x 6mm2  |  |  |
| Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 5733 with Fuselink to BS1362  Patents and Trademarks Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.   | Product Class 1  | Must be earthed   |  |  |
| Maximum Installation Altitude  2000m  Standard/Approval  BS 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.   | Ambient Operating Temperature  | -5° to +40°C  |  |  |
| Standard/Approval  BS 5733 with Fuselink to BS1362  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  | Recommended Location   | Internal Use Only   |  |  |
| Patents and Trademarks  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  | Maximum Installation Altitude  | 2000m   |  |  |
| Patents and Trademarks  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428  Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.   | Standard/Approval  | BS 5733 with Fuselink to BS1362   |  |  |
| European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.   | Patents and Trademarks   | CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 |  |  |
|  | European standard and the product information is   |   | as part of our development programme. Therefore, we reserve the right to alter designs |  |
|  | the limitations of reproduction and printing process and are not binding.                                | guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 16 October 2018 04:06 PM<br>E&OE   |  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









