




LRXJ12BC-PBW

Linea-Rondo CFX Bright Chrome Frame/Polished Brass Front 1 gang RJ12 Outlet - Unshielded White

Item Image	Wiring	Dimensions																																																								
	 <table border="1" data-bbox="808 646 966 730"> <thead> <tr> <th>Pin</th> <th>Color</th> <th>Wire Color</th> <th>Socket</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>NO USER</td> <td>NO USER</td> <td>NO USER</td> </tr> <tr> <td>1</td> <td>GREEN / White</td> <td>BLUE</td> <td>NO USER</td> </tr> <tr> <td>2</td> <td>ORANGE / White</td> <td>YELLOW</td> <td>NO USER</td> </tr> <tr> <td>3</td> <td>WHITE / Blue</td> <td>GREEN</td> <td>NO USER</td> </tr> <tr> <td>4</td> <td>BLUE / White</td> <td>RED</td> <td>NO USER</td> </tr> <tr> <td>5</td> <td>WHITE / Orange</td> <td>BLACK</td> <td>NO USER</td> </tr> <tr> <td>6</td> <td>WHITE / Green</td> <td>WHITE</td> <td>NO USER</td> </tr> <tr> <td>7</td> <td>NO USER</td> <td>NO USER</td> <td>NO USER</td> </tr> <tr> <td>8</td> <td>NO USER</td> <td>NO USER</td> <td>NO USER</td> </tr> <tr> <td>9</td> <td>NO USER</td> <td>NO USER</td> <td>NO USER</td> </tr> <tr> <td>10</td> <td>NO USER</td> <td>NO USER</td> <td>NO USER</td> </tr> <tr> <td>11</td> <td>NO USER</td> <td>NO USER</td> <td>NO USER</td> </tr> <tr> <td>12</td> <td>NO USER</td> <td>NO USER</td> <td>NO USER</td> </tr> </tbody> </table>	Pin	Color	Wire Color	Socket	0	NO USER	NO USER	NO USER	1	GREEN / White	BLUE	NO USER	2	ORANGE / White	YELLOW	NO USER	3	WHITE / Blue	GREEN	NO USER	4	BLUE / White	RED	NO USER	5	WHITE / Orange	BLACK	NO USER	6	WHITE / Green	WHITE	NO USER	7	NO USER	NO USER	NO USER	8	NO USER	NO USER	NO USER	9	NO USER	NO USER	NO USER	10	NO USER	NO USER	NO USER	11	NO USER	NO USER	NO USER	12	NO USER	NO USER	NO USER	 <p>Hamilton® LINEA RONDO CFX J12 1 gang RJ12 Outlet Unshielded 6 wire</p>
Pin	Color	Wire Color	Socket																																																							
0	NO USER	NO USER	NO USER																																																							
1	GREEN / White	BLUE	NO USER																																																							
2	ORANGE / White	YELLOW	NO USER																																																							
3	WHITE / Blue	GREEN	NO USER																																																							
4	BLUE / White	RED	NO USER																																																							
5	WHITE / Orange	BLACK	NO USER																																																							
6	WHITE / Green	WHITE	NO USER																																																							
7	NO USER	NO USER	NO USER																																																							
8	NO USER	NO USER	NO USER																																																							
9	NO USER	NO USER	NO USER																																																							
10	NO USER	NO USER	NO USER																																																							
11	NO USER	NO USER	NO USER																																																							
12	NO USER	NO USER	NO USER																																																							

Primary Range	Linea-Rondo CFX
Insert Type	1 gang RJ12 Outlet - Unshielded
Plate Finish	Linea-Rondo CFX Bright Chrome Frame/Polished Brass
Insert Colour	White
EAN13 Barcode	5017504490553
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	N/A
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5 x 1mm ²
Earth Terminal Capacity 2	4 x 1.5mm ²
Earth Terminal Capacity 3	3 x 2.5mm ²
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand
Earth Terminal Capacity 5	1 x 6mm ²
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350

<p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p>	<p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>	<p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p>
<p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>	<p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p>	<p>Correct as at 16 October 2018 04:06 PM E&OE</p>

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM1238