




LRXJ12PB-BSB

Linea-Rondo CFX Polished Brass Frame/Bright Steel Front 1 gang RJ12 Outlet - Unshielded Black

Item Image	Wiring	Dimensions																																				
	 <table border="1" data-bbox="808 646 966 730"> <thead> <tr> <th>Pin</th> <th>Color</th> <th>Wire Color</th> <th>Socket</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>GREEN</td> <td>White</td> <td>BLUE</td> </tr> <tr> <td>2</td> <td>ORANGE</td> <td>White</td> <td>YELLOW</td> </tr> <tr> <td>3</td> <td>WHITE</td> <td>Blue</td> <td>GREEN</td> </tr> <tr> <td>4</td> <td>BLUE</td> <td>White</td> <td>RED</td> </tr> <tr> <td>5</td> <td>WHITE</td> <td>Orange</td> <td>BLACK</td> </tr> <tr> <td>6</td> <td>White</td> <td>Green</td> <td>WHITE</td> </tr> <tr> <td>7</td> <td>NO USE</td> <td>NO USE</td> <td>NO USE</td> </tr> <tr> <td>8</td> <td>NO USE</td> <td>NO USE</td> <td>NO USE</td> </tr> </tbody> </table>	Pin	Color	Wire Color	Socket	1	GREEN	White	BLUE	2	ORANGE	White	YELLOW	3	WHITE	Blue	GREEN	4	BLUE	White	RED	5	WHITE	Orange	BLACK	6	White	Green	WHITE	7	NO USE	NO USE	NO USE	8	NO USE	NO USE	NO USE	 <p style="text-align: center;">Hamilton® LINEA RONDO CFX J12 1 gang RJ12 Outlet Unshielded 6 wire</p>
Pin	Color	Wire Color	Socket																																			
1	GREEN	White	BLUE																																			
2	ORANGE	White	YELLOW																																			
3	WHITE	Blue	GREEN																																			
4	BLUE	White	RED																																			
5	WHITE	Orange	BLACK																																			
6	White	Green	WHITE																																			
7	NO USE	NO USE	NO USE																																			
8	NO USE	NO USE	NO USE																																			

Primary Range	Linea-Rondo CFX	
Insert Type	1 gang RJ12 Outlet - Unshielded	
Plate Finish	Linea-Rondo CFX Polished Brass Frame/Bright Steel	
Insert Colour	Black	
EAN13 Barcode	5017504431556	
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm ²	
Earth Terminal Capacity 2	4 x 1.5mm ²	
Earth Terminal Capacity 3	3 x 2.5mm ²	
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand	
Earth Terminal Capacity 5	1 x 6mm ²	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 04:06 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM1238