Hamilton

making connections beautifully

에 감사가 가지 않는 것 것이 없는 것이 없다.	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio
LRXJ45CB-CBB		
Linea-Rondo CFX Copper Bronze Frame/Copper Bronze Front 1 gang RJ45 CAT 5E Outlet - Unshielded Black		
Item Image	Wiring	Dimensions
	RMS CATES Raw View	LINEA RONDO CEX J45 1 gang RJ45 -CAT 5E Outlet Unshielded 8 wire
Primary Range	Linea-Rondo CFX	
Insert Type	1 gang RJ45 CAT 5E Outlet - Unshielded	
Plate Finish	Linea-Rondo CFX Copper Bronze Frame/Copper Bronze	
Insert Colour	Black	
EAN13 Barcode	5017504058104	
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
EuroFix Additional Notes	Can be used in both EIA 568A and EIA 568B wiriing schedules	
Patents and Trademarks	Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 04:06 P E&O
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered i E: info@hamilton-litestat.com www.hamilton-litestat.com Registered i	toad, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB n London No. 941624 VAT Registration No. 222 6607 84	Listed in Strimbe LUCKINS relector DSFDus CRI. No. 101128

SL