## Hamilton

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRXKELSN-SSB Linea-Rondo CFX Satin Nickel Frame/Satin Steel Front 1 gang 20AX 2 Way Key switch EMG LTG TEST Black Item Image Wiring Dimensions Hemilton KEL 2 Way Key switch EMG LTG TEST 91.5 Primary Range Linea-Rondo CFX Insert Type 1 gang 20AX 2 Way Key Switch EMG LTG TEST Plate Finish Linea-Rondo CFX Satin Nickel Frame/Satin Steel Insert Colour Black EAN13 Barcode 5017504526108 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Single Current Rating 20AX 220/250V AC Voltage 20 Amp inductive Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm **Terminal Capacity 1** 5 x 1mm2 **Terminal Capacity 2** 4 x 1.5mm2 **Terminal Capacity 3** 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Internal Use Only **Recommended Location** Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All accessories are manufactured under an accredited All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System as part of our development programme Therefore, we reserve the right to alter designs correct at the time of going to press. and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 16 October 2018 04:07 PM guarantee an exact colour match and shadings of the limitations of reproduction and printing E&OE process and are not binding. of certain finishes. R Hamilton & Co Ltd. Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimble **SECA** T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

SL

LRXKELSN-SSB - Linea-Rondo CFX Satin Nickel Frame/Satin Steel Front 1 gang 20AX 2 Way Key switch EMG LTG TEST Black

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio