

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRXR21PB-SBW

Primary Range Linea-Rondo CFX Insert Type 1 gang 10AX 2 Way Rocker Plate Finish Linea-Rondo CFX Polished Brass Frame/Satin Brass Insert Colour EAN13 Barcode 5017504413217 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Current Rating 10AX Voltage 10AX Voltage 10AX Voltage 10AX Voltage 10AMp inductive Mains Frequency 10A Maximum Load 10Amp inductive Mains Frequency 10A Maximum 10A Maring 10A Maximum 10A Maring 192XD 10A Maximum 10A Maring 10A Maximum 10A Maring 192XD 10A Maximum 10A Maring 10A Maximum 10A Maximum 10A Maring 10A Maximum 10A Maximum 10A Maring 10A Maximum 10A Maxi	Dimensions Hemilton LINEA RONDO CFX R21 2 Way Rocker
Primary Range Linea-Rondo CFX Insert Type 1 gang 10AX 2 Way Rocker Plate Finish Linea-Rondo CFX Polished Brass Frame/Satin Brass Insert Colour Polished Brass/White EAN13 Barcode 5017504413217 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	R21
Insert Type 1 gang 10AX 2 Way Rocker Plate Finish Linea-Rondo CFX Polished Brass Frame/Satin Brass Insert Colour Polished Brass/White EAN13 Barcode 5017504413217 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 1P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Plate Finish Linea-Rondo CFX Polished Brass Frame/Satin Brass Insert Colour Polished Brass/White EAN13 Barcode 5017504413217 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Insert Colour	
EAN13 Barcode 5017504413217 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2	
Terminal Capacity 1 5 x 1mm2	
Terminal Capacity 2 4 x 1.5mm2	
Terminal Capacity 3 1 x 2.5mm2	
Terminal Capacity 4 1 x 4mm2 Multi-strand	
Terminal Capacity 5 1 x 6mm2	
Earth Terminal Capacity 1 5 x 1mm2	
Earth Terminal Capacity 2 4 x 1.5mm2	
Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5 1 x 6mm2	
Product Class 1 Must be earthed	
Ambient Operating Temperature -5° to +40°C	
Recommended Location Internal Use Only	
Maximum Installation Altitude 2000m	
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Commu Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=	
European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. as par correct at the time of going to press. Therefore,	cy of the company to improve products to four development programme. The very entry to alter designs dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. R Hamilton & Co Ltd. Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ	Correct as at 16 October 2018 04:07 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio