

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## LRXR21SN-SSW

Linea-Rondo CFX Satin Nick	LRXR21SN-SSW kel Frame/Satin Steel Front 1 gang 10AX 2 V	Vay Rocker Satin Steel/White
Item Image	Wiring	Dimensions
	Abernate 2 Tays setting  Loop in Long Out  Intermodate settings	LINEA RONDO CFX R21 2 Way Rocker
Primary Range	Linea-Rondo CFX	
Insert Type	1 gang 10AX 2 Way Rocker	
Plate Finish	Linea-Rondo CFX Satin Nickel Frame/Satin Steel	
Insert Colour	Satin Steel/White	
EAN13 Barcode	5017504527211	
Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	25mm	
Switched Poles	Single	
Current Rating	10AX	
Voltage	220/250V AC	
Maximum Load	10 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	1 x 2.5mm2	
Terminal Capacity 4	1 x 4mm2 Multi-strand	
Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval Patents and Trademarks	BS EN 60669-1  Linea is a Registered Trade Mark No 2398665  CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428	
All products listed conform to current British or European standard and the product information is	Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.  BS EN ISO 9001: 2015 Quality Management System.  BS EN ISO 9001: 2015 Quality Management System.	
correct at the time of going to press.  Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Therefore, we reserve the right to alter designs and dimensions without prior notice.  Correct as at 16 October 2018 04:07 PM E&OE
P Hamilton & Co. Ltd. Unit 10 Carrick Business Centre. 4-5 Bonville Bo	of certain finishes.	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio