

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

LRXR22PB-SSW

Item Image Wiring Dimensions Historia Javania Javani	Linea-Rondo CFX Polished Brass Frame/Satin Steel Front 2 gang 10AX 2 Way Rocker Polished Brass/White			
Pirmary Range Linea-Rondo CFX Insert Type 2 gang 10AV 2 Way Rocker Pilmary Plane Pilmon Linea-Rondo CFX Polluted Brass FamouSairo Steel Insert Type 2 gang 10AV 2 Way Rocker Pilmon Linea-Rondo CFX Polluted Brass FamouSairo Steel Insert Colour Pollute Brass-White EANN-3 Bancade S0770644501 Sorgie Height = 91.5mm Width = 91.5mm Depth = 4.0mm Pilmon Box Depth Somman Wall Wall Wall Wall Wall Wall Wall Wa				
Primary Range Linea-Rondo CFX Indert Type 2 gang 10X 2 Wily Rocker Polished Brass White Inner Colour Polished Brass Frame/Satin Steel Inner Colour Polished Brass Frame/Satin Steel Inner Colour Polished Brass Frame/Satin Steel Inner Colour Polished Brass White Earth Stancole Stroke 44, 2021 Single Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Hole Centres Bas Rondon = 90.5mm Grid Fixing = CFX Clips Minimum Wall Blox Depth 25mm Seltented Poles Single Coursen Rating 10AX Voltage 2020/250V AC Maximum Load 10 Am prinductive Maximum Load In Amplitude Maximum Single Poly Single Coursen Rating In Poly Single Coursen Rating In Poly Single Course Rating In Poly Single Si	Item Image	Wiring	Dimensions	
Insert Type 2 gang 10AX 2 Way Rocker Plate Finish		Abernative 2 very weedings	R22 2 Way Rocker	
Pate Finish	Primary Range	Linea-Rondo CFX		
Insert Colour	Insert Type	2 gang 10AX 2 Way Rocker		
EAN13 Barcode 5017504443221 Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm Fixing Holo Centres Minimum Wall Box Depth 25mm Switched Poles Single 10AX Votage 220250V AC Maximum Load 10 Amp inductive Mains Frequency 10 Amp inductive Mains Frequency 10 Amp inductive Starting 10 Amp inductive Mains Frequency 10 Amp inductive	Plate Finish	Linea-Rondo CFX Polished Brass Frame/Satin Steel		
Dimensions (Nominal) Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm	Insert Colour	Polished Brass/White		
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating 1P2XD Contact Gap Minimum 3mm Cerninal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 3 1 x 4mm2 Multi-strand Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Tearth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 E	EAN13 Barcode	5017504443221		
Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency Finance Finance Formace Softitz Freminal Capacity 1 Ferminal Capacity 1 Ferminal Capacity 1 Ferminal Capacity 1 Ferminal Capacity 2 Ferminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 Farth Terminal Capacity 1 Farth Terminal Capacity 1 Farth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Farth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 5 x 1mm2 Farth Terminal Capacity 3 5 x 2.5mm2 Farth Terminal Capacity 3 5 x 2.5mm2 Farth Terminal Capacity 3 5 x 2.5mm2 Farth Terminal Capacity 3 6 x 2.5mm2 Farth Terminal Capacity 3 7 x 6mm2 Forduct Class 1 Ambient Operating Temperature 5 x 1 x 6mm2 Forduct Class 1 Ambient Operating Temperature 5 x 1 x 6mm2 Forduct Class 1 All products listed conform to current British or European standard and the product information is cornect at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 901: 2015 Quality Management System. Forducts listed conform to current British or European standard and the products information is cornect at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 901: 2015 Quality Management System. Forducts listed or of the company to improve products the manufactured under an accredited BS EN ISO 900: 2016 Qua	Dimensions (Nominal)	Single: Height = 91.5mm Width = 91.5mm Depth = 4.0mm		
Switched Poles Current Rating 10AX Voltage 120/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 2 1x 4mm2 Multi-strand Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 3 1x 2.5mm2 Earth Terminal Capacity 3 1x 2.5mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Ter	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating Voltage 220/250V AC Maximum Load Maximum Load 10 Amp inductive 50Hz IP Rating IP2XD Contact Gap Minimum 3mm 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9 In x 6mm2 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Cap	Minimum Wall Box Depth	25mm		
Voltage 220/250V AC Maximum Load 10 Amp Inductive Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 1x 2.5mm2 Terminal Capacity 4 1x 4mm2 Multi-strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 5x 1mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 1x 4mm2 Multi-strand Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 6 1x 4mm2 Multi-strand Earth Terminal Capacity 7 1x 4mm2 Multi-strand Earth Terminal Capacity 8 1x 4mm2 Multi-strand Earth Terminal Capacity 9 1x 6mm2 Froduct Class 1 5x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature 5x 0x40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Megistered Trade Mark No 2398667 Patents and Trademarks Linea is a Registered Trade Mark No 2398667 European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All corrects are the time of going to press. BS EN ISO 901: 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notics. Therefore, we reserve the right to alter designs and dimensions without prior notics. EXCE	Switched Poles	Single		
Maximum Load Mains Frequency 50Hz IP Rating IP Rati	Current Rating	10AX		
Mains Frequency Frequency Frating Frating Frequency Frequency Fresting Fresting Freminal Capacity 1 Freminal Capacity 2 Freminal Capacity 3 Freminal Capacity 3 Freminal Capacity 4 Freminal Capacity 4 Freminal Capacity 4 Freminal Capacity 5 Freminal Capacity 5 Freminal Capacity 1 Freminal Capacity 1 Freminal Capacity 1 Freminal Capacity 2 Freminal Capacity 2 Freminal Capacity 3 Freminal Capacity 4 Freminal Capacity 4 Freminal Capacity 4 Freminal Capacity 5 Freminal Capacity 4 Freminal Capacity 5 Freminal Capacity 5 Freminal Capacity 6 Freminal Capacity 6 Freminal Capacity 6 Freminal Capacity 7 Freminal Capacity 8 Freminal Capacity 8 Freminal Capacity 9 Fremi	Voltage	220/250V AC		
PRating IP2XD	Maximum Load	10 Amp inductive		
Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 I x 4mm2 Multi-strand Earth Terminal Capacity 5 I x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 I x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 I x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Te	Mains Frequency	50Hz		
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 Aubient Operating Temperature 5 to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. B EN 60001: 2015 Quality Management System. All confidence of the company to improve products as part of our development programme. Therefore, we reserve the right to after designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04.07 PM EXCOR	IP Rating	IP2XD		
Terminal Capacity 2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5-5 to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Billustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot the Roce E&CE E	Contact Gap Minimum	3mm		
Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Todacity 4 Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BEN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dinensions without prior notice. BEN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dinensions without prior notice. EXOC	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx 4mm2 Multi-strand Earth Terminal Capacity 6 Earth Terminal Capacity 6 Tx 4mm2 Multi-strand Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Tx 4mm2 Multi-strand Earth Terminal Capacity 8 Tx 4mm2 Multi-strand Earth Terminal Capacity 8 Tx 4mm2 Multi-strand Earth Terminal Capacity 9 Tx 4mm2 Multi-strand E	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Maximum Installation Altitude Standard/Approval Bas EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All approducts listed conform to current British or European standard and the product information is correct at the time of going to press. Bas EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04:07 PM E&CE	Terminal Capacity 3	1 x 2.5mm2		
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 I x 4mm2 Multi-strand Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to manufacturing processes we cannot guarantee an exact colour match and shadings of EXCEPTION TO THE PROCESSOR OF THE PROCES	Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398665 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 04-07 PM EACH	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature Ambient Operating Temperature Fecommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All stratement of going to press. BLIDEATE OF THE OFFICE OF THE OFFICE OF THE OFFICE OF THE OFFICE	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of EXCENTIAN Ammunity Terminal Capacity 5 1 x 4mm2 Multi-strand 1 x 4mm2 Multi-strand 1 x 6mm2 2000m BS EN 6069-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM EXCENTIANCE Correct as at 16 October 2018 04:07 PM EXCENTIANCE EXCENTIANCE Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04:07 PM EXCENTIANCE EXCENTIANCE Therefore, we reserve the right to alter designs and dimensions without prior notice. EXCENTIANCE Therefore, we reserve the right to alter designs and dimensions without prior notice. EXCENTIANCE Therefore, we reserve the right to alter designs and dimensions without prior notice. EXCENTIANCE Therefore, we reserve the right to alter designs and dimensions without prior notice. EXCENTIANCE Therefore, we reserve the right to alter designs and dimensions without prior notic	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM EACE	Earth Terminal Capacity 3	3 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM guarantee an exact colour match and shadings of	Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM E&OE	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Ullustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM E&OE	Product Class 1	Must be earthed		
Maximum Installation Altitude Standard/Approval BS EN 60669-1 Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM E&OE	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS EN 60669-1 Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 16 October 2018 04:07 PM E&OE	Recommended Location	Internal Use Only		
Patents and Trademarks Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04:07 PM guarantee an exact colour match and shadings of	Maximum Installation Altitude	2000m		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 Linea-Rondo CFX is a UK Registered Design Certificate No: R21=2106349 SS2=2106350 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of CFX is a Registered Trade Mark No. 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 16 October 2018 04:07 PM guarantee an exact colour match and shadings of	Standard/Approval	BS EN 60669-1		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	Patents and Trademarks	ents and Trademarks CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Community Trd Mark No. 002906428		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 16 October 2018 04:07 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio